Product datasheet

Specification





servo motor BCH, Lexium 28, 130mm, 2000W, 13.5kg.cm², with oil seal, with key, straight connection

BCH2MM2023CA6C

Main

Range compatibility	Lexium 28	
Device short name	BCH2	
Product or component type	Servo motor	

Complementary

Complementary		
Maximum mechanical speed	3000 rpm	
[Us] rated supply voltage	220 V	
Network number of phases	Three phase	
Continuous stall current	9.95 A	
Continuous stall torque	9.55 N.m for LXM26D at 12 A, 220 V, three phase 9.55 N.m for LXM28 at 12 A, 220 V, three phase 9.55 N.m	
Continuous power	2000 W	
Peak stall torque	28.65 N.m for LXM26D at 12 A, 220 V, three phase 28.65 N.m for LXM28 at 12 A, 220 V, three phase 28.65 N.m	
Nominal output power	2000 W for LXM26D at 12 A, 220 V, three phase 2000 W for LXM28 at 12 A, 220 V, three phase 2000 W	
Nominal torque	9.55 N.m for LXM26D at 12 A, 220 V, three phase 9.55 N.m for LXM28 at 12 A, 220 V, three phase 9.55 N.m	
Nominal speed	2000 rpm 2000 rpm for LXM26D at 12 A, 220 V, three phase 2000 rpm for LXM28 at 12 A, 220 V, three phase	
Maximum current Irms	32.85 A for LXM28 at 2 kW, 220 V 32.85 A at 2 kW, 220 V	
Maximum permanent current	11.25 A	
Product compatibility	LXM26D servo drive motor at 2 kW, 220 V, three phase LXM28 servo drive motor at 2 kW, 220 V, three phase	
Shaft end	Keyed	
Shaft diameter	22 mm	
Shaft length	55 mm	
Key width	8 mm	
Feedback type	20 bits single turn absolute encoder	
Holding brake	Without	
mounting support	Asian standard flange	

Motor flange size	130 mm
Electrical connection	Connector MIL
Torque constant	0.96 N.m/A at 20 °C
Back emf constant	58 V/krpm at 20 °C
Rotor inertia	13.5 kg.cm ²
Stator resistance	0.34 Ohm at 20 °C
Stator inductance	4.5 mH at 20 °C
Stator electrical time constant	13.24 ms at 20 °C
Maximum radial force Fr	670 N at 2000 rpm
Maximum axial force Fa	200 N
Brake pull-in power	19.7 W
Type of cooling	Natural convection
Length	187 mm
Number of motor stacks	4
Centring collar diameter	110 mm
Centring collar depth	8 mm
Number of mounting holes	4
Mounting holes diameter	9.2 mm
Circle diameter of the mounting holes	145 mm
Distance shaft shoulder-flange	8 mm
Net weight	9.7 kg

Environment

IP degree of protection	IP50 IM V3 IP65 IM B5, IM V1	
Ambient air temperature for operation	-2040 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.5 cm
Package 1 Width	23.3 cm
Package 1 Length	36.1 cm
Package 1 Weight	11.021 kg
Unit Type of Package 2	S06
Number of Units in Package 2	9
Package 2 Height	73.5 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	111.0 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
②	Mercury Free	
②	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards


Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Circularity Profile	End of Life Information	

BCH2MM2023CA6C

Dimensions Drawings

Dimensions

Dimensions of Motor



	mm	in.
L (without holding brake)	187	7.36
L (with holding brake)	216	8.5
Z	134.5	5.30


BCH2MM2023CA6C

Performance Curves

Torque/Speed Curves with 230 V Three Phase Supply Voltage

Servo Motor with LXM28AU20●●● Servo Drive





- 1: Peak torque
- 2: Continuous torque