

# BCH2MR3021CF6C

servo motor BCH, Lexium 28, 180mm, 3000W, 54.1kg.cm<sup>2</sup>, without oil seal, with key, brake, straight connection



## Main

Range Compatibility	Lexium 28
Device short name	BCH2
Product or Component Type	Servo motor

## Complementary

Maximum mechanical speed	3000 rpm
[Us] rated supply voltage	220 V
Phase	Three phase
Continuous stall current	16.33 A
Continuous stall torque	126.74 lbf.in (14.32 N.m) LXM28... 19.8 A, 220 V, three phase
Continuous power	3000 W
Peak stall torque	380.32 lbf.in (42.97 N.m) LXM28... 19.8 A, 220 V, three phase
Nominal output power	3000 W LXM28... 19.8 A, 220 V, three phase
Nominal torque	126.74 lbf.in (14.32 N.m) LXM28... 19.8 A, 220 V, three phase
Nominal speed	2000 rpm LXM28... 19.8 A, 220 V, three phase
Maximum current Irms	53.9 A LXM28... 3 kW, 220 V
Maximum permanent current	18.8 A
Product compatibility	LXM28... servo drive 3 kW, 220 V, three phase
Shaft end	Keyed
Shaft diameter	1.4 in (35 mm)
Shaft length	3.1 in (79 mm)
Key width	0.4 in (10 mm)
Feedback type	20 bits single turn absolute encoder
Holding brake	With
Holding torque	424.8 lbf.in (48 N.m) built-in
Mounting Support	Asian standard flange
Motor flange size	7.09 in (180 mm)
Electrical connection	Connector MIL
Torque constant	0.88 N.m/A 68 °F (20 °C)
Back emf constant	53 V/krpm 68 °F (20 °C)
Rotor inertia	54.1 kg.cm <sup>2</sup>
Stator resistance	0.131 Ohm 68 °F (20 °C)
Stator inductance	2.7 mH 68 °F (20 °C)
Stator electrical time constant	20.61 ms 68 °F (20 °C)
Maximum radial force Fr	1200 N 2000 rpm
Maximum axial force Fa	497 N
Brake pull-in power	49.6 W

Type of cooling	Natural convection
Length	9.3 in (235 mm)
Number of motor stacks	2
Centring collar diameter	4.5 in (114.3 mm)
Centring collar depth	0.2 in (4 mm)
Number of mounting holes	4
Mounting holes diameter	0.5 in (13.5 mm)
Circle diameter of the mounting holes	7.9 in (200 mm)
Distance shaft shoulder-flange	0.2 in (4 mm)
Net Weight	50.7 lb(US) (23 kg)

## Environment

IP Degree of Protection	IP54 IM B5, IM V1 IP50 IM V3
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)





## Ordering and shipping details

Category	US1PC5318281
Discount Schedule	PC53
GTIN	3606480734793
Returnability	No
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.6 in (24.5 cm)
Package 1 Width	11.4 in (29.0 cm)
Package 1 Length	23.03 in (58.5 cm)
Package 1 Weight	54.30 lb(US) (24.63 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.