Product datasheet

Specifications





servo motor BCH - 180mm - 3000W - w oil seal - w key - brake - straight con

BCH2MR3023CF6C

Main

Range compatibility	Lexium 28
Device short name	BCH2
Product or component type	Servo motor

Complementary

3000 rpm
220 V
Three phase
16.33 A
14.32 N.m for LXM26D at 19.8 A, 220 V, three phase 14.32 N.m for LXM28 at 19.8 A, 220 V, three phase
3000 W
42.97 N.m for LXM26D at 19.8 A, 220 V, three phase 42.97 N.m for LXM28 at 19.8 A, 220 V, three phase
3000 W for LXM26D at 19.8 A, 220 V, three phase 3000 W for LXM28 at 19.8 A, 220 V, three phase
14.32 N.m for LXM26D at 19.8 A, 220 V, three phase 14.32 N.m for LXM28 at 19.8 A, 220 V, three phase
2000 rpm for LXM26D at 19.8 A, 220 V, three phase 2000 rpm for LXM28 at 19.8 A, 220 V, three phase
53.9 A for LXM26D at 3 kW, 220 V 53.9 A for LXM28 at 3 kW, 220 V
18.8 A
LXM26D servo drive motor at 3 kW, 220 V, three phase LXM28 servo drive motor at 3 kW, 220 V, three phase
Keyed
35 mm
79 mm
10 mm
20 bits single turn absolute encoder
With
48 N.m built-in
Asian standard flange
180 mm
Connector MIL

Torque constant	0.88 N.m/A at 20 °C
Back emf constant	53 V/krpm at 20 °C
Rotor inertia	54.1 kg.cm²
Stator resistance	0.131 Ohm at 20 °C
Stator inductance	2.7 mH at 20 °C
Stator electrical time constant	20.61 ms at 20 °C
Maximum radial force Fr	1200 N at 2000 rpm
Maximum axial force Fa	497 N
Brake pull-in power	49.6 W
Type of cooling	Natural convection
Length	235 mm
Number of motor stacks	2
Centring collar diameter	114.3 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	13.5 mm
Circle diameter of the mounting holes	200 mm
Distance shaft shoulder-flange	4 mm
Net weight	23 kg

Environment

IP degree of protection	IP50 IM V3 IP65 IM B5, IM V1	
Ambient air temperature for operation	040 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	29 cm
Package 1 Length	58.5 cm
Package 1 Weight	24630 g
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	50 cm
Package 2 Width	80 cm
Package 2 Length	60 cm
Package 2 Weight	110.7 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
②	Mercury Free	
Ø	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards


Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Circularity Profile	End of Life Information	

BCH2MR3023CF6C

Dimensions Drawings

Dimensions

Dimensions of Motor




	mm	in.
L (without holding brake)	202	7.95
L (with holding brake)	235	9.25
A	79	3.11
С	73	2.87
D	35	1.38
F	63	2.48
N	28	1.10
М	M12	
R	30	1.18
V	10	0.39
W	10	0.39
Z	136	5.35

Performance Curves

Torque/Speed Curves with 230 V Three Phase Supply Voltage

Servo Motor with LXM28AU30●●● Servo Drive



- 1: Peak torque
- 2: Continuous torque