




PRODUCT-DETAILS

BEA26/325

BEA26/325 Connecting Link



General Information	
Extended Product Type	BEA26/325
Product ID	1SBN082406R1001
EAN	3471522199362
Catalog Description	BEA26/325 Connecting Link
Long Description	BEA26/325 is an insulated connecting link used to connect A26 3-pole contactors with the MS325 manual motor starters. The BEA26/325 ensures the electrical connection between a contactor and the associated manual motor starter.

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Popular Downloads	
Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and	FPTC407775P0001

Manuals

Dimensions	
Product Net Width	54 mm
Product Net Depth / Length	65 mm
Product Net Height	40 mm
Product Net Weight	0.031 kg

Technical	
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Terminal Type	Screw Terminals
Suitable For	MS325 A26
Product Name	Connecting Link

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
Declaration of Conformity - CE	1SBD250835U1000
Declaration of Conformity - UKCA	1SBD250836U1000
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001

Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	190 mm
Package Level 1 Height	60 mm
Package Level 1 Gross Weight	0.31 kg
Package Level 1 EAN	3471522199362

External Classifications and Standards	
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology

ETIM 9	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

