Specifications





Circuit breaker, PowerPacT B, 40A, 3 pole, 600Y/347VAC, 18kA, lugs, thermal magnetic, 80%

BGM36040

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2,016.00 USD

Main

Range	PowerPact
Product name	PowerPact B
Device short name	BG 040
Product or Component Type	Circuit breaker
Device Application	Distribution

Complementary

Complementary	
Line Rated Current	40 A
Number of Poles	3P
Control Type	Toggle
Breaking capacity code	G
Breaking capacity	65 kA 208Y/120 V AC 50/60 Hz UL 489 65 kA 240 V AC 50/60 Hz UL 489 35 kA 480/277 V AC 50/60 Hz UL 489 35 kA 480 V AC 50/60 Hz UL 489 18 kA 250 V DC UL 489 20 kA 600Y/347 V AC 50/60 Hz UL 489
[Ue] rated operational voltage	525 V AC 50/60 Hz UL 489
Network Frequency	50/60 Hz
[Ics] rated service breaking capacity	65 kA 220240 V AC 50/60 Hz IEC 60947-2 18 kA 500525 V AC 50/60 Hz IEC 60947-2 35 kA 380415 V AC 50/60 Hz IEC 60947-2 35 kA 440 V AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2
Trip unit technology	Thermal-magnetic
Continuous current rating	80 %
[Ui] rated insulation voltage	800 V IEC 60947-2
Suitability for isolation	Yes IEC 60947-2
Utilisation category	Category A
Mechanical durability	20000 cycles IEC 947-1 Annex K ed 5.2
Electrical durability	10000 cycles IEC 947-1 Annex K ed 5.2 440 V In
Connection pitch	1.06 in (27 mm)
AWG gauge	AWG 6AWG 2/0 fine stranded aluminium/copper AWG 14AWG 3/0 rigid or stranded aluminium/copper

AWG 14...AWG 3/0 rigid or stranded aluminium/copper

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Local signalling	Presence of auxiliary contacts flag green)	
Mounting mode	Clip-on 35 x 15 mm symmetrical DIN rail) By screws plate)	
Electrical connection	Everlink lug, line Terminal nut, load	
Tightening torque	44.3 lbf.in (5 N.m) 0.0040.02 in² (2.516 mm²) (AWG 14AWG 4) 79.7 lbf.in (9 N.m) 0.040.1 in² (2595 mm²) (AWG 3AWG 3/0)	
Number of slots	1 auxiliary switch OF plug-in) 1 voltage release MN or MX plug-in) 1 alarm switch SD plug-in)	
Power wire stripping length	0.8 in (20 mm)	
Color	Gray RAL 7016)	
9 mm pitches	9	
Height	5.4 in (137 mm)	
Width	3.2 in (81 mm)	
Depth	3.1 in (80 mm)	
Net Weight	2.368 lb(US) (1.074 kg)	
Quantity per Set	Set of 1	
Circuit breaker application	HACR rated	

Environment

Quality labels	CE
Standards	NEMA AB1
	GB 14048.2
	EN/IEC 60947-2
	EN/IEC 60947-5-1
	UL 489
	NMX J-266
	CSA C22.2 No 5
Product certifications	UL
	IEC
	CCC
	EAC
	CSA
	NOM
IP degree of protection	Front cover IP40 IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 IEC 60947-1
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)
Operating altitude	< 6561.68 ft (2000 m) without derating
	5000 m with derating

Ordering and shipping details

Category	US10DE201131
Discount Schedule	0DE2
GTIN	785901621584
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.4 in (13.7 cm)
Package 1 Width	3.2 in (8.1 cm)
Package 1 Length	3.1 in (8.0 cm)
Package 1 Weight	3.0005 lb(US) (1.361 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance




Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	"WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"

Product data sheet

Technical Illustration

Dimensions



(M) TERMINATION OPTION - EverLink (ON end) / Terminal Nut (OFF end) ALL DIMENSIONS ARE APPROXIMATE. ALSO REFER TO CAD, TECHNICAL DRAWINGS, AND DOCUMENTATION