Specifications

Green



Circuit breaker, PowerPacT B, 30A, 2 pole, 600Y/347VAC, 25kA, I-Line, thermal magnetic, 80%, CA

BJA260305

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,541.00 USD

Main

Range	PowerPact	
Product name	PowerPact B	
Device short name	BJ 030	
Product or Component Type	Circuit breaker	
Device Application	Distribution	

Complementary

Complementary		
Line Rated Current	30 A	
Number of Poles	2P	
Control Type	Toggle	
Breaking capacity code	J	
Breaking capacity	100 kA 208Y/120 V AC 50/60 Hz UL 489 100 kA 240 V AC 50/60 Hz UL 489 65 kA 480/277 V AC 50/60 Hz UL 489 65 kA 480 V AC 50/60 Hz UL 489 25 kA 600Y/347 V AC 50/60 Hz UL 489 50 kA 250 V DC UL 489	
[Ue] rated operational voltage	690 V AC 50/60 Hz UL 489	
Network Frequency	50/60 Hz	
[Ics] rated service breaking capacity	100 kA 220240 V AC 50/60 Hz IEC 60947-2 25 kA 500525 V AC 50/60 Hz IEC 60947-2 2.5 kA 690 V AC 50/60 Hz IEC 60947-2 65 kA 380415 V AC 50/60 Hz IEC 60947-2 65 kA 440 V AC 50/60 Hz IEC 60947-2	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2	
Trip unit technology	Thermal-magnetic	
Continuous current rating	80 %	
[Ui] rated insulation voltage	800 V IEC 60947-2	
Suitability for isolation	Yes IEC 60947-2	
Utilisation category	Category A	
Mechanical durability	20000 cycles IEC 947-1 Annex K ed 5.2	
Electrical durability	10000 cycles IEC 947-1 Annex K ed 5.2 440 V In	
Connection pitch	1.06 in (27 mm)	
AWG gauge	AWG 14AWG 2/0 aluminium/copper	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Local signalling	Presence of auxiliary contacts flag green)	
Mounting mode	I-Line	
Electrical connection	I-Line connection, line Lugs, load	
Mounting Height	3.000000000 in (76.2 mm)	
Tightening torque	31.938.9 lbf.in (3.64.4 N.m) 0.0040.009 in² (2.56 mm²) (AWG 14AWG 10) 44.354.9 lbf.in (56.2 N.m) 0.020.1 in² (1070 mm²) (AWG 8AWG 2/0)	
Number of slots	1 auxiliary switch OF plug-in) 1 voltage release MN or MX plug-in)	
Power wire stripping length	0.8 in (20 mm)	
Color	Gray RAL 7016)	
9 mm pitches	6	
Height	5.4 in (137 mm)	
Width	2.1 in (54 mm)	
Depth	3.5 in (89 mm)	
Net Weight	2.099 lb(US) (0.952 kg)	
Quantity per Set	Set of 1	
Phase connection	CA	
Circuit breaker application	HACR rated	

Environment

Quality labels	CE	
Standards	UL 489 GB 14048.2 EN/IEC 60947-5-1 NMX J-266 CSA C22.2 No 5 EN/IEC 60947-2 NEMA AB1	
Product certifications	UL IEC CCC EAC CSA NOM	
IP degree of protection	Front cover IP40 IEC 60529	
IK degree of protection	IK07 conforming to IEC 62262	
Pollution degree	3 IEC 60947-1	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)	
Operating altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating	

Ordering and shipping details

Category	US10DE201135	
Discount Schedule	0DE2	
GTIN	3606486281765	
Returnability	Yes	

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.4 in (13.7 cm)
Package 1 Width	2.1 in (5.4 cm)
Package 1 Length	3.5 in (8.9 cm)
Package 1 Weight	2.899 lb(US) (1.315 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Product data sheet

Technical Illustration

Dimensions

