

# Product datasheet

Specifications



servo motor BMH - 1.4 Nm - 8000 rpm - untapped shaft - with brake - IP54

BMH0701T06F1A

Discontinued on: 9 Feb 2023

Discontinued

EAN Code: 3606485194196

## Main

|                           |                                                                                                              |
|---------------------------|--------------------------------------------------------------------------------------------------------------|
| Device short name         | BMH                                                                                                          |
| Product or component type | Servo motor                                                                                                  |
| Maximum mechanical speed  | 8000 rpm                                                                                                     |
| Continuous stall torque   | 1.4 N.m for LXM32.U90M2 at 3 A, 230 V, single phase<br>1.4 N.m for LXM32.D18M2 at 6 A, 115 V, single phase   |
| Peak stall torque         | 4 N.m for LXM32.U90M2 at 3 A, 230 V, single phase<br>4.2 N.m for LXM32.D18M2 at 6 A, 115 V, single phase     |
| Nominal output power      | 450 W for LXM32.U90M2 at 3 A, 230 V, single phase<br>350 W for LXM32.D18M2 at 6 A, 115 V, single phase       |
| Nominal torque            | 1.1 N.m for LXM32.U90M2 at 3 A, 230 V, single phase<br>1.35 N.m for LXM32.D18M2 at 6 A, 115 V, single phase  |
| Nominal speed             | 4000 rpm for LXM32.U90M2 at 3 A, 230 V, single phase<br>2500 rpm for LXM32.D18M2 at 6 A, 115 V, single phase |
| Product compatibility     | LXM32.D18M2 at 115 V single phase<br>LXM32.U90M2 at 230 V single phase                                       |
| Shaft end                 | Smooth shaft                                                                                                 |
| IP degree of protection   | IP54 standard                                                                                                |
| Speed feedback resolution | 32768 points/turn                                                                                            |
| Holding brake             | With                                                                                                         |
| mounting support          | International standard flange                                                                                |
| Electrical connection     | Straight connectors                                                                                          |

## Complementary

|                           |                                                |
|---------------------------|------------------------------------------------|
| Range compatibility       | Lexium 32                                      |
| [Us] rated supply voltage | 240 V                                          |
| Network number of phases  | Three phase                                    |
| Continuous stall current  | 2.85 A                                         |
| Continuous power          | 1.05 W                                         |
| Maximum current Irms      | 9.6 A for LXM32.D18M2<br>9.6 A for LXM32.U90M2 |
| Maximum permanent current | 9.56 A                                         |
| Second shaft              | Without second shaft end                       |
| Shaft diameter            | 11 mm                                          |
| Shaft length              | 23 mm                                          |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Feedback type                         | Single turn SinCos Hiperface                                                                                               |
| Holding torque                        | 3 N.m holding brake                                                                                                        |
| Motor flange size                     | 70 mm                                                                                                                      |
| Number of motor stacks                | 1                                                                                                                          |
| Torque constant                       | 0.49 N.m/A at 120 °C                                                                                                       |
| Back emf constant                     | 31.17 V/krpm at 120 °C                                                                                                     |
| Number of motor poles                 | 10                                                                                                                         |
| Rotor inertia                         | 0.7 kg.cm <sup>2</sup>                                                                                                     |
| Stator resistance                     | 3.2 Ohm at 20 °C                                                                                                           |
| Stator inductance                     | 9.1 mH at 20 °C                                                                                                            |
| Stator electrical time constant       | 2.8 ms at 20 °C                                                                                                            |
| Maximum radial force Fr               | 660 N at 1000 rpm<br>520 N at 2000 rpm<br>460 N at 3000 rpm<br>410 N at 4000 rpm<br>380 N at 5000 rpm<br>360 N at 6000 rpm |
| Maximum axial force Fa                | 0.2 x Fr                                                                                                                   |
| Brake pull-in power                   | 7 W                                                                                                                        |
| Type of cooling                       | Natural convection                                                                                                         |
| Length                                | 161 mm                                                                                                                     |
| Centring collar diameter              | 60 mm                                                                                                                      |
| Centring collar depth                 | 2.5 mm                                                                                                                     |
| Number of mounting holes              | 4                                                                                                                          |
| Mounting holes diameter               | 5.5 mm                                                                                                                     |
| Circle diameter of the mounting holes | 82 mm                                                                                                                      |
| Net weight                            | 2.6 kg                                                                                                                     |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 11.0 cm |
| Package 1 Width              | 20.0 cm |
| Package 1 Length             | 40.0 cm |
| Package 1 Weight             | 2.8 kg  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

Well-being performance

|                                                                                                              |     |
|--------------------------------------------------------------------------------------------------------------|-----|
|  Mercury Free               |     |
|  Rohs Exemption Information | Yes |
|  Pvc Free                   |     |

Certifications & Standards

|                          |                                                                                                                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)                                                                  |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                               |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations                                                                                    |

Dimensions Drawings

Servo Motors Dimensions

Example with Straight Connectors



- a: Power supply for servo motor brake
- b: Power supply for servo motor encoder
- (1) Shaft end, keyed slot (optional)

Dimensions in mm

| Straight connectors |      | Rotatable angled connectors |      | c (without brake) | c (with brake) | c1 | c2 | c3  | h    | h1                                  | Ø     | Ø1 for screws |
|---------------------|------|-----------------------------|------|-------------------|----------------|----|----|-----|------|-------------------------------------|-------|---------------|
| b1                  | b2   | b1                          | b2   |                   |                |    |    |     |      |                                     |       |               |
| 39.5                | 25.5 | 39.5                        | 39.5 | 122               | 161            | 23 | 18 | 2.5 | 4 h9 | 12.5 <sup>+0</sup> <sub>-0.13</sub> | 11 k6 | M4 x 14       |

Dimensions in in.


| Straight connectors |    | Rotatable angled connectors |      | c (without brake) | c (with brake) | c1   | c2   | c3   | h       | h1                                    | Ø       | Ø1 for screws |
|---------------------|----|-----------------------------|------|-------------------|----------------|------|------|------|---------|---------------------------------------|---------|---------------|
| b1                  | b2 | b1                          | b2   |                   |                |      |      |      |         |                                       |         |               |
| 1.55                | 1  | 1.55                        | 1.55 | 4.80              | 6.33           | 0.90 | 0.70 | 0.09 | 0.16 h9 | 0.49 <sup>+0</sup> <sub>-0.0051</sub> | 0.43 k6 | M4 x 0.55     |

Performance Curves

115 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32-D18M2 servo drive




- X    Speed in rpm
- Y    Torque in Nm
- 1    Peak torque
- 2    Continuous torque

230 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•U90M2 servo drive



- X    Speed in rpm
- Y    Torque in Nm
- 1    Peak torque
- 2    Continuous torque