


BMH1401P02A2A

servo motor BMH, Lexium 32, 10.3Nm,
4000rpm, untapped shaft, without brake, IP54,
128 multiturn encoder



Commercial status

End-of-Sale Notice : JUN 30, 2023

End-of-Sale Notice

Main

Product or component type	Servo motor
Device short name	BMH
Maximum mechanical speed	4000 Rpm
Continuous stall torque	10.3 N.M for LXM32.D30M2 at 10 A, 230 V, single phase 10.3 N.M for LXM32.D30N4 at 10 A, 400 V, three phase 10.3 N.M for LXM32.D30N4 at 10 A, 480 V, three phase
Peak stall torque	30.8 N.M for LXM32.D30M2 at 10 A, 230 V, single phase 30.8 N.M for LXM32.D30N4 at 10 A, 400 V, three phase 30.8 N.M for LXM32.D30N4 at 10 A, 480 V, three phase
Nominal output power	1450 W for LXM32.D30M2 at 10 A, 230 V, single phase 2400 W for LXM32.D30N4 at 10 A, 400 V, three phase 2400 W for LXM32.D30N4 at 10 A, 480 V, three phase
Nominal torque	6.9 N.M for LXM32.D30M2 at 10 A, 230 V, single phase 7.7 N.M for LXM32.D30N4 at 10 A, 400 V, three phase 7.7 N.M for LXM32.D30N4 at 10 A, 480 V, three phase
Nominal speed	2000 rpm for LXM32.D30M2 at 10 A, 230 V, single phase 3000 rpm for LXM32.D30N4 at 10 A, 400 V, three phase 3000 rpm for LXM32.D30N4 at 10 A, 480 V, three phase
Product compatibility	LXM32.D30M2 at 230 V single phase LXM32.D30N4 at 400...480 V three phase
Shaft end	Smooth shaft
IP degree of protection	IP54 standard
Speed feedback resolution	131072 points/turn x 4096 turns
Holding brake	Without
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

Complementary

Range compatibility	Lexium 32
[Us] rated supply voltage	480 V
Network number of phases	Three phase
Continuous stall current	8.58 A
Continuous power	2.85 W
Maximum current Irms	29.8 A for LXM32.D30M2 29.8 A for LXM32.D30N4
Maximum permanent current	29.8 A

Second shaft	Without second shaft end
Shaft diameter	24 Mm
Shaft length	50 Mm
Feedback type	Multiturn SinCos Hiperface
Motor flange size	140 Mm
Number of motor stacks	1
Torque constant	1.2 N.M/A at 120 °C
Back emf constant	77.4 V/Krpm at 120 °C
Number of motor poles	10
Rotor inertia	16.46 Kg.Cm ²
Stator resistance	0.69 Ohm at 20 °C
Stator inductance	6.7 MH at 20 °C
Stator electrical time constant	9.7 Ms at 20 °C
Maximum radial force Fr	1930 N at 1000 rpm 1530 N at 2000 rpm 1340 N at 3000 rpm
Maximum axial force Fa	0.2 x Fr
Type of cooling	Natural convection
Length	152 Mm
Centring collar diameter	130 Mm
Centring collar depth	3.5 Mm
Number of mounting holes	4
Mounting holes diameter	11 Mm
Circle diameter of the mounting holes	165 Mm
Product weight	8 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.0 Cm
Package 1 Width	26.0 Cm
Package 1 Length	60.0 Cm
Package 1 Weight	8.3 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commercialisation**