Product datasheet

Specifications





servo motor BMH, Lexium 32, 62.5Nm, 3800rpm, untapped shaft, with brake, IP65, IP67, 16 multiturn encoder

BMH2052P27F2A

Main

Device short name	вмн	
Product or component type	Servo motor	
Maximum mechanical speed	3800 rpm	
Continuous stall torque	62.5 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 62.5 N.m for LXM32.D72N4 at 24 A, 480 V, three phase	
Peak stall torque	170 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 170 N.m for LXM32.D72N4 at 24 A, 480 V, three phase	
Nominal output power	6500 W for LXM32.D72N4 at 24 A, 400 V, three phase 6500 W for LXM32.D72N4 at 24 A, 480 V, three phase	
Nominal torque	41.6 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 41.6 N.m for LXM32.D72N4 at 24 A, 480 V, three phase	
Nominal speed	1500 rpm for LXM32.D72N4 at 24 A, 400 V, three phase 1500 rpm for LXM32.D72N4 at 24 A, 480 V, three phase	
Product compatibility	LXM32.D72N4 at 400480 V three phase	
Shaft end	Smooth shaft	
IP degree of protection	IP65 standard IP67 with IP67 kit	
Speed feedback resolution	32768 points/turn x 4096 turns	
Holding brake	With	
mounting support	International standard flange	
Electrical connection	Rotatable right-angled connectors	

Complementary

Range compatibility	Lexium 32	
[Us] rated supply voltage	480 V	
Network number of phases	Three phase	
Continuous stall current	24.2 A	
Continuous power	7.85 W	
Maximum current Irms	72 A for LXM32.D72N4	
Maximum permanent current	96.8 A	
Second shaft	Without second shaft end	
Shaft diameter	38 mm	
Shaft length	80 mm	
Feedback type	Multiturn SinCos Hiperface	

Holding torque	80 N.m holding brake	
Motor flange size	205 mm	
Number of motor stacks	2	
Torque constant	2.6 N.m/A at 120 °C	
Back emf constant	161 V/krpm at 120 °C	
Number of motor poles	10	
Rotor inertia	145 kg.cm²	
Stator resistance	0.3 Ohm at 20 °C	
Stator inductance	5.6 mH at 20 °C	
Stator electrical time constant	18.7 ms at 20 °C	
Maximum radial force Fr	4200 N at 1000 rpm 3330 N at 2000 rpm 2910 N at 3000 rpm	
Maximum axial force Fa	0.2 x Fr	
Brake pull-in power	40 W	
Type of cooling	Natural convection	
Length	454.5 mm	
Centring collar diameter	180 mm	
Centring collar depth	4 mm	
Number of mounting holes	4	
Mounting holes diameter	noles diameter 14 mm	
Circle diameter of the mounting holes	215 mm	
Net weight	48.9 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	36.0 cm
Package 1 Width	31.0 cm
Package 1 Length	73.0 cm
Package 1 Weight	58.0 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations