# **Product datasheet**

Specification





# isolated analog output module X80 - 4 outputs - severe

BMXAMO0410H

#### Main

Range of product	Modicon X80
Product or component type	Analog output module
Product specific application	For severe environments
Electrical connection	20 ways 1 connector
Isolation between channels	Isolated

## Complementary

Measurement error	0.1 % of full scale 25 °C
	<= 0.45 % of full scale - 2570 °C
Temperature drift	45 ppm/°C +/- 10 V
	45 ppm/°C 020 mA
	45 ppm/°C 420 mA
Minimum crosstalk attenuation	80 dB
Common mode rejection	100 dB
Isolation voltage	1400 V DC between channels and ground
	1400 V DC between channels and bus
	750 V DC between channels
Detection type	Open circuit 020 mA
	Open circuit 420 mA
	Short circuit +/- 10 V
Load impedance ohmic	>= 1000 Ohm +/- 10 V
	<= 500 Ohm 020 mA
	<= 500 Ohm 420 mA
Output level	High level
Analogue output number	4
Analogue output type	Current: 020 mA
	Current: 420 mA
	Voltage: +/- 10 V
Analogue output resolution	15 bits + sign
Supply	Internal power supply via rack
Conversion time	<= 1 ms
Maximum conversion value	021 mA 020 mA
	021 mA 420 mA
	+/- 10.5 V +/- 10 V
Fallback mode	Configurable
	Predefined
MTBF reliability	1000000 H
Operating altitude	02000 m
	20005000 m with derating factor

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Status LED	1 LED (green) RUN 1 LED per channel (green) channel diagnostic 1 LED (red) ERR 1 LED (red) I/O
Net weight	0.15 kg
Power consumption in W	3 W 24 V DC typical 3.6 W 24 V DC maximum 0.45 W 3.3 V DC typical 0.51 W 3.3 V DC maximum
Current consumption	150 mA at 3.3 V DC 140 mA at 24 V DC

## **Environment**

Vibration resistance	3 gn
Shock resistance	30 gn
ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-2570 °C
Relative humidity	595 % at 55 °C without condensation
IP degree of protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Product certifications	CE RCM CSA EAC Merchant Navy UL ATEX IEC-Ex
Standards	EN/IEC 61010-2-201 EN/IEC 61131-2 UL 61010-2-201 CSA C22.2 No 61010-2-201
Environmental characteristic	Gas resistant class Gx Gas resistant class 3C4 Dust resistant class 3S4 Sand resistant class 3S4 Salt resistant level 2 Mold growth resistant class 3B2 Fungal spore resistant class 3B2 Hazardous location
protective treatment	Conformal coating

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	11.600 cm
Package 1 Length	11.800 cm
Package 1 Weight	222.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm

Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3 624 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**


Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific wast collection and never end up in rubbish bins	
Circularity Profile	End of Life Information	

Jul 17, 2024

#### **Dimensions Drawings**

#### **Modules Mounted on Racks**

#### **Dimensions**




- (1) With removable terminal block (cage, screw or spring).
- (2) With FCN connector.
- (3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.

Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81

#### BMXAMO0410H

#### Connections and Schema

#### Wiring Diagram



U/lx + pole input for channel x COMx - pole input for channel x Channel 0 Voltage actuator Channel 1 Current actuator

The current loop is self-powered by the output and does not request any external supply.