



AC servo motor BSH, Lexium 05, 0.7N.m, 8000rpm, untapped shaft, without brake, IP65

BSH0701T21A2A

! Discontinued on: 01-Nov-2020

(!) Discontinued

Main

Device short name	BSH							
Product or component type	Servo motor							
Maximum mechanical speed	8000 rpm							
Continuous stall torque	1.3 N.m for LXM32.U90M2 at 3 A, 230 V, single phase 1.4 N.m for LXM05AD10M3X, 200240 V, three phase 1.4 N.m for LXM05BD10M3X, 200240 V, three phase 1.4 N.m for LXM05CD10M3X, 200240 V, three phase 1.4 N.m for LXM05CD10M3X, 230 V, single phase 1.4 N.m for LXM05AD10F1, 110120 V, single phase 1.4 N.m for LXM05AD17M2, 200240 V, single phase 1.4 N.m for LXM05BD10F1, 110120 V, single phase 1.4 N.m for LXM05BD17M2, 200240 V, single phase 1.4 N.m for LXM05CD10F1, 110120 V, single phase 1.4 N.m for LXM05CD10F1, 110120 V, single phase 1.4 N.m for LXM05CD17M2, 200240 V, single phase 1.4 N.m for LXM05CD17M2, 200240 V, single phase 1.5 N.m for LXM05CD17M2, 200240 V, single phase 1.5 N.m for LXM15LU60N4, 400 V, three phase 1.6 N.m for LXM15LU60N4, 480 V, three phase 1.7 N.m for LXM15LU60N4, 230 V, three phase 1.8 N.m for LXM15LD10N4, 230 V, three phase 1.9 N.m for LXM15LD10N4, 480 V, three phase 1.9 N.m for LXM15LD10N4, 480 V, three phase 1.9 N.m for LXM15LD10N4, 230 V, three phase 1.9 N.m for LXM15LD10N4, 230 V, three phase 1.9 N.m for LXM15LD10N4, 230 V, three phase 1.9 N.m for LXM15LD13M3, 230 V, three phase 1.9 N.m for LXM15LD21M3, 230 V, three phase							

Peak stall torque

3.5 N.m for LXM32.U90M2 at 3 A, 230 V, single phase 3.19 N.m for LXM15LD13M3, 230 V, single phase 2.42 N.m for LXM05AD10F1, 110...120 V, single phase 3.19 N.m for LXM05AD17M2, 200...240 V, single phase 2.42 N.m for LXM05BD10F1, 110...120 V, single phase 3.19 N.m for LXM05BD17M2, 200...240 V, single phase 2.42 N.m for LXM05CD10F1, 110...120 V, single phase 3.19 N.m for LXM05CD17M2, 200...240 V, single phase 3.5 N.m for LXM32.D18M2 at 6 A, 115 V, single phase 1.9 N.m for LXM15LU60N4, 400 V, three phase 1.9 N.m for LXM15LU60N4, 480 V, three phase 1.9 N.m for LXM15LU60N4, 230 V, three phase 2.91 N.m for LXM15LD10N4, 230 V, three phase 2.91 N.m for LXM15LD10N4, 400 V, three phase 2.91 N.m for LXM15LD10N4, 480 V, three phase 3.19 N.m for LXM15LD13M3, 230 V, three phase 3.19 N.m for LXM15LD21M3, 230 V, three phase 2.42 N.m for LXM05AD10M3X, 200...240 V, three phase 3.19 N.m for LXM05AD17M3X, 200...240 V, three phase 2.42 N.m for LXM05BD10M3X, 200...240 V, three phase 3.19 N.m for LXM05BD17M3X, 200...240 V, three phase $2.42\ \text{N.m}$ for LXM05CD10M3X, 200...240 V, three phase 3.19 N.m for LXM05CD17M3X, 200...240 V, three phase

Nominal output power

500 W for LXM32.U90M2 at 3 A, 230 V, single phase 350 W for LXM32.D18M2 at 6 A, 115 V, single phase 400 W for LXM05AD10M3X, 200...240 V, three phase 400 W for LXM05BD10M3X, 200...240 V, three phase 400 W for LXM05CD10M3X, 200...240 V, three phase 380 W for LXM05AD10F1, 110...120 V, single phase 380 W for LXM05BD10F1, 110...120 V, single phase 380 W for LXM05CD10F1, 110...120 V, single phase 400 W for LXM05AD17M2, 200...240 V, single phase 400 W for LXM05BD17M2, 200...240 V, single phase 400 W for LXM05CD17M2, 200...240 V, single phase 654 W for LXM15LD13M3, 230 V, single phase 1000 W for LXM15LD10N4, 400 V, three phase 1000 W for LXM15LD10N4, 480 V, three phase 400 W for LXM05AD17M3X, 200...240 V, three phase 400 W for LXM05BD17M3X, 200...240 V, three phase 400 W for LXM05CD17M3X 200 240 V three phase 440 W for LXM15LU60N4, 230 V, three phase 564 W for LXM15LD10N4, 230 V, three phase 586 W for LXM15LU60N4, 400 V, three phase 586 W for LXM15LU60N4, 480 V, three phase 654 W for LXM15LD13M3, 230 V, three phase 654 W for LXM15LD21M3, 230 V, three phase

Nominal torque

0.94 N.m for LXM32.U90M2 at 3 A, 230 V, single phase 1.25 N.m for LXM15LD13M3, 230 V, single phase 1.36 N.m for LXM32.D18M2 at 6 A, 115 V, single phase 0.7 N.m for LXM15LU60N4, 230 V, three phase 0.7 N.m for LXM15LU60N4, 400 V, three phase 0.7 N.m for LXM15LU60N4, 480 V, three phase 1.23 N.m for LXM15LD10N4, 400 V, three phase 1.23 N.m for LXM15LD10N4, 480 V, three phase 1.25 N.m for LXM15LD10N4, 230 V, three phase 1.25 N.m for LXM15LD10N4, 230 V, three phase 1.25 N.m for LXM15LD13M3, 230 V, three phase 1.25 N.m for LXM15LD13M3, 230 V, three phase 1.25 N.m for LXM15LD13M3, 230 V, three phase

Nominal speed

5000 rpm for LXM32.U90M2 at 3 A, 230 V, single phase 3000 rpm for LXM05AD10F1, 110...120 V, single phase 3000 rpm for LXM05BD10F1, 110...120 V, single phase 3000 rpm for LXM05CD10F1, 110...120 V, single phase 3000 rpm for LXM05AD10M3X, 200...240 V, three phase 3000 rpm for LXM05BD10M3X, 200...240 V, three phase 3000 rpm for LXM05CD10M3X, 200...240 V, three phase 8000 rpm for LXM15LD10N4, 400 V, three phase $\stackrel{\cdot}{\text{3000}}$ rpm for LXM05AD17M2, 200...240 V, single phase 3000 rpm for LXM05BD17M2, 200...240 V, single phase 3000 rpm for LXM05CD17M2, 200...240 V, single phase 3000 rpm for LXM05AD17M3X, 200...240 V, three phase 3000 rpm for LXM05BD17M3X, 200...240 V, three phase 3000 rpm for LXM05CD17M3X, 200...240 V, three phase 5000 rpm for LXM15LD13M3, 230 V, single phase 2500 rpm for LXM32.D18M2 at 6 A, 115 V, single phase 5000 rpm for LXM15LD10N4, 230 V, three phase 5000 rpm for LXM15LD13M3, 230 V, three phase 5000 rpm for LXM15LD21M3, 230 V, three phase 6000 rpm for LXM15LU60N4, 230 V, three phase 8000 rpm for LXM15LD10N4, 480 V, three phase 8000 rpm for LXM15LU60N4, 400 V, three phase 8000 rpm for LXM15LU60N4, 480 V, three phase

Product compatibility	LXM05AD10F1 at 110120 V single phase
	LXM05AD17M2 at 200240 V single phase
	LXM05BD10F1 at 110120 V single phase LXM05BD17M2 at 200240 V single phase
	LXM05CD10F1 at 110120 V single phase
	LXM05CD17M2 at 200240 V single phase
	LXM15LD13M3 at 230 V single phase
	LXM32.U90M2 at 230 V single phase
	LXM32.D18M2 at 115 V single phase
	LXM15LU60N4 at 230 V three phase
	LXM05AD10M3X at 200240 V three phase
	LXM05BD10M3X at 200240 V three phase LXM05CD10M3X at 200240 V three phase
	LXM15LD13M3 at 230 V three phase
	LXM15LU60N4 at 400 V three phase
	LXM15LU60N4 at 480 V three phase
	LXM15LD10N4 at 400 V three phase
	LXM05AD17M3X at 200240 V three phase
	LXM05BD17M3X at 200240 V three phase
	LXM05CD17M3X at 200240 V three phase
	LXM15LD10N4 at 230 V three phase
	LXM15LD10N4 at 480 V three phase
	LXM15LD21M3 at 230 V three phase
Shaft end	Untapped
IP degree of protection	IP65 standard
	IP67 with IP67 kit
Current for allocate manufactures	101070 : 1.11
Speed feedback resolution	131072 points/turn
Holding brake	Without
mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors
Complementary Range compatibility	Lexium 15
go oopaaay	Lexium 32
	Lexium 05
supply voltage max	480 V
Network number of phases	Three phase
Continuous stall current	3.2 A
maximum continuous power	1.06 W
Maximum current Irms	10 A for LXM32.D18M2
	9 A for LXM32.U90M2
	9.9 A for LXM15LD13M3
	9.9 A for LXM15LD21M3 9.9 A for LXM15LU60N4
	9.9 A for LXM15LD10N4
Maximum permanent current	
Maximum permanent current Switching frequency	9.9 A for LXM15LD10N4
<u> </u>	9.9 A for LXM15LD10N4 10.1 A
Switching frequency	9.9 A for LXM15LD10N4 10.1 A 8 kHz
Switching frequency Second shaft	9.9 A for LXM15LD10N4 10.1 A 8 kHz Without second shaft end
Switching frequency Second shaft Shaft diameter	9.9 A for LXM15LD10N4 10.1 A 8 kHz Without second shaft end 11 mm
Switching frequency Second shaft Shaft diameter Shaft length	9.9 A for LXM15LD10N4 10.1 A 8 kHz Without second shaft end 11 mm 23 mm
Switching frequency Second shaft Shaft diameter Shaft length Feedback type	9.9 A for LXM15LD10N4 10.1 A 8 kHz Without second shaft end 11 mm 23 mm Single turn SinCos Hiperface
Switching frequency Second shaft Shaft diameter Shaft length Feedback type Motor flange size	9.9 A for LXM15LD10N4 10.1 A 8 kHz Without second shaft end 11 mm 23 mm Single turn SinCos Hiperface 70 mm
Switching frequency Second shaft Shaft diameter Shaft length Feedback type Motor flange size Number of motor stacks	9.9 A for LXM15LD10N4 10.1 A 8 kHz Without second shaft end 11 mm 23 mm Single turn SinCos Hiperface 70 mm

LXM05AD10F1 at 110...120 V single phase

Product compatibility

Number of motor poles

6

Rotor inertia	0.25 kg.cm ²
Stator resistance	3.3 Ohm at 20 °C
Stator inductance	12.3 mH at 20 °C
Stator electrical time constant	3.73 ms at 20 °C
Maximum radial force Fr	360 N at 6000 rpm 380 N at 5000 rpm 410 N at 4000 rpm 460 N at 3000 rpm 520 N at 2000 rpm 660 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Type of cooling	Natural convection
Length	154 mm
Centring collar diameter	60 mm
Centring collar depth	2.5 mm
Number of mounting holes	4
Mounting holes diameter	5.5 mm
Circle diameter of the mounting holes	82 mm
Net weight	2.2 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.3 cm
Package 1 Width	12.8 cm
Package 1 Length	37.7 cm
Package 1 Weight	2.1 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

BSH0701T21A2A

Dimensions Drawings

Servo Motors Dimensions

Example with Straight Connectors



- a: Power supply for servo motor brake
- b: Power supply for servo motor encoder
- (1) M4 screw
- (2) Shaft end, keyed slot (optional)

Dimensions in mm

Straight Rotatable angle connectors connectors		•	c (without	c (with	c1	c2	сЗ	h	h1	Ø	Ø1 for	
b1	b2	b1	b2	brake)	brake)							screws
39.5	25.5	39.5	39.5	154	180	23	18	2.5	4 N9	2.5 ^{+0.1} ₀	11 k6	M4 x 10

Dimensions in in.

Straigh		Rotatal angled connec		(without	c (with brake)	c1	c2	с3	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2									
1.55	1.00	1.55	1.55	6.06	7.08	0.90	0.70	0.09	0.16 N9	0.01 ^{+0.004} 0	0.43 k6	M4 x 0.39


BSH0701T21A2A

Performance Curves

115 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D18M2 servo drive




- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque

230 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•U90M2 servo drive



- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque