

Product data sheet

Specifications



servo motor BSH, Lexium 05,
7.8N.m, 2500rpm, 100mm, keyed
shaft, Sincos multi turn, without
brake, IP65

BSH1003P32A2A

Product availability: Stock - Normally stocked in distribution facility

Price*: 2,090.00 USD

Main

Device short name	BSH
Product or Component Type	Servo motor
Maximum mechanical speed	6000 rpm
Continuous stall torque	70.8 lbf.in (8 N.m) LXM32.D30N4 10 A, 400 V, three phase 70.8 lbf.in (8 N.m) LXM32.D30N4 10 A, 480 V, three phase 69.04 lbf.in (7.8 N.m) LXM05CD28M2, 200...240 V, single phase 69.04 lbf.in (7.8 N.m) LXM05AD28M2, 200...240 V, single phase 69.04 lbf.in (7.8 N.m) LXM05BD28M2, 200...240 V, single phase 69.04 lbf.in (7.8 N.m) LXM05BD34N4, 380...480 V, three phase 69.04 lbf.in (7.8 N.m) LXM05BD42M3X, 200...240 V, three phase 69.04 lbf.in (7.8 N.m) LXM05CD34N4, 380...480 V, three phase 69.04 lbf.in (7.8 N.m) LXM05CD42M3X, 200...240 V, three phase 59.3 lbf.in (6.7 N.m) LXM15LD21M3, 230 V, three phase 59.3 lbf.in (6.7 N.m) LXM15LD17N4, 230 V, three phase 59.3 lbf.in (6.7 N.m) LXM15LD17N4, 400 V, three phase 59.3 lbf.in (6.7 N.m) LXM15LD17N4, 480 V, three phase 69.04 lbf.in (7.8 N.m) LXM15LD28M3, 230 V, three phase 69.04 lbf.in (7.8 N.m) LXM15MD28N4, 400 V, three phase 69.04 lbf.in (7.8 N.m) LXM15MD28N4, 480 V, three phase 69.04 lbf.in (7.8 N.m) LXM15MD40N4, 400 V, three phase 69.04 lbf.in (7.8 N.m) LXM15MD40N4, 480 V, three phase 69.04 lbf.in (7.8 N.m) LXM05AD34N4, 380...480 V, three phase 69.04 lbf.in (7.8 N.m) LXM05AD42M3X, 200...240 V, three phase
Peak stall torque	250.5 lbf.in (28.3 N.m) LXM32.D30N4 10 A, 400 V, three phase 250.5 lbf.in (28.3 N.m) LXM32.D30N4 10 A, 480 V, three phase 174.27 lbf.in (19.69 N.m) LXM05AD28M2, 200...240 V, single phase 174.27 lbf.in (19.69 N.m) LXM05BD28M2, 200...240 V, single phase 174.27 lbf.in (19.69 N.m) LXM05CD28M2, 200...240 V, single phase 137.2 lbf.in (15.5 N.m) LXM15LD21M3, 230 V, three phase 110.6 lbf.in (12.5 N.m) LXM15LD17N4, 230 V, three phase 110.6 lbf.in (12.5 N.m) LXM15LD17N4, 400 V, three phase 110.6 lbf.in (12.5 N.m) LXM15LD17N4, 480 V, three phase 174.27 lbf.in (19.69 N.m) LXM15LD28M3, 230 V, three phase 174.27 lbf.in (19.69 N.m) LXM15MD28N4, 400 V, three phase 174.27 lbf.in (19.69 N.m) LXM15MD28N4, 480 V, three phase 205.07 lbf.in (23.17 N.m) LXM15MD40N4, 400 V, three phase 205.07 lbf.in (23.17 N.m) LXM15MD40N4, 480 V, three phase 203.66 lbf.in (23.01 N.m) LXM05AD34N4, 380...480 V, three phase 205.07 lbf.in (23.17 N.m) LXM05AD42M3X, 200...240 V, three phase 203.66 lbf.in (23.01 N.m) LXM05BD34N4, 380...480 V, three phase 205.07 lbf.in (23.17 N.m) LXM05BD42M3X, 200...240 V, three phase 203.66 lbf.in (23.01 N.m) LXM05CD34N4, 380...480 V, three phase 205.07 lbf.in (23.17 N.m) LXM05CD42M3X, 200...240 V, three phase

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nominal output power	2000 W LXM32.D30N4 10 A, 400 V, three phase
	2600 W LXM32.D30N4 10 A, 480 V, three phase
	1100 W LXM05AD28M2, 200...240 V, single phase
	1100 W LXM05BD28M2, 200...240 V, single phase
	1100 W LXM05CD28M2, 200...240 V, single phase
	1100 W LXM05AD42M3X, 200...240 V, three phase
	1100 W LXM05BD42M3X, 200...240 V, three phase
	1100 W LXM05CD42M3X, 200...240 V, three phase
	1300 W LXM15LD28M3, 230 V, three phase
	1700 W LXM15LD17N4, 230 V, three phase
	1700 W LXM15LD21M3, 230 V, three phase
	1800 W LXM05AD34N4, 380...480 V, three phase
	1800 W LXM05BD34N4, 380...480 V, three phase
	1800 W LXM05CD34N4, 380...480 V, three phase
	2000 W LXM15MD28N4, 400 V, three phase
	2000 W LXM15MD40N4, 400 V, three phase
	2200 W LXM15LD17N4, 400 V, three phase
	2200 W LXM15MD28N4, 480 V, three phase
	2200 W LXM15MD40N4, 480 V, three phase
	2300 W LXM15LD17N4, 480 V, three phase
Nominal torque	55.8 lbf.in (6.3 N.m) LXM32.D30N4 10 A, 400 V, three phase
	55.8 lbf.in (6.3 N.m) LXM32.D30N4 10 A, 480 V, three phase
	32.7 lbf.in (3.7 N.m) LXM15LD17N4, 480 V, three phase
	59.57 lbf.in (6.73 N.m) LXM05AD28M2, 200...240 V, single phase
	59.57 lbf.in (6.73 N.m) LXM05BD28M2, 200...240 V, single phase
	59.57 lbf.in (6.73 N.m) LXM05CD28M2, 200...240 V, single phase
	40.7 lbf.in (4.6 N.m) LXM15MD28N4, 480 V, three phase
	40.7 lbf.in (4.6 N.m) LXM15MD40N4, 480 V, three phase
	41.6 lbf.in (4.7 N.m) LXM15LD17N4, 400 V, three phase
	44.3 lbf.in (5 N.m) LXM15MD28N4, 400 V, three phase
	44.3 lbf.in (5 N.m) LXM15MD40N4, 400 V, three phase
	50.4 lbf.in (5.7 N.m) LXM05AD34N4, 380...480 V, three phase
	50.4 lbf.in (5.7 N.m) LXM05BD34N4, 380...480 V, three phase
	50.4 lbf.in (5.7 N.m) LXM05CD34N4, 380...480 V, three phase
	53.1 lbf.in (6 N.m) LXM15LD17N4, 230 V, three phase
	53.1 lbf.in (6 N.m) LXM15LD21M3, 230 V, three phase
	55.8 lbf.in (6.3 N.m) LXM15LD28M3, 230 V, three phase
	59.57 lbf.in (6.73 N.m) LXM05AD42M3X, 200...240 V, three phase
	59.57 lbf.in (6.73 N.m) LXM05BD42M3X, 200...240 V, three phase
	59.57 lbf.in (6.73 N.m) LXM05CD42M3X, 200...240 V, three phase
Nominal speed	3000 rpm LXM32.D30N4 10 A, 400 V, three phase
	4000 rpm LXM32.D30N4 10 A, 480 V, three phase
	4500 rpm LXM15LD17N4, 400 V, three phase
	6000 rpm LXM15LD17N4, 480 V, three phase
	1500 rpm LXM05AD28M2, 200...240 V, single phase
	1500 rpm LXM05BD28M2, 200...240 V, single phase
	1500 rpm LXM05CD28M2, 200...240 V, single phase
	1500 rpm LXM05AD42M3X, 200...240 V, three phase
	1500 rpm LXM05BD42M3X, 200...240 V, three phase
	1500 rpm LXM05CD42M3X, 200...240 V, three phase
	2000 rpm LXM15LD28M3, 230 V, three phase
	2500 rpm LXM15LD17N4, 230 V, three phase
	2500 rpm LXM15LD21M3, 230 V, three phase
	3000 rpm LXM05AD34N4, 380...480 V, three phase
	3000 rpm LXM05BD34N4, 380...480 V, three phase
	3000 rpm LXM05CD34N4, 380...480 V, three phase
	4000 rpm LXM15MD28N4, 400 V, three phase
	4000 rpm LXM15MD40N4, 400 V, three phase
	4500 rpm LXM15MD28N4, 480 V, three phase
	4500 rpm LXM15MD40N4, 480 V, three phase

Product compatibility	LXM05AD28M2 200...240 V single phase LXM05BD28M2 200...240 V single phase LXM05CD28M2 200...240 V single phase LXM15LD21M3 230 V three phase LXM05AD42M3X 200...240 V three phase LXM05BD42M3X 200...240 V three phase LXM05CD42M3X 200...240 V three phase LXM15LD17N4 230 V three phase LXM15LD17N4 400 V three phase LXM15LD17N4 480 V three phase LXM15LD28M3 230 V three phase LXM05AD34N4 380...480 V three phase LXM05BD34N4 380...480 V three phase LXM05CD34N4 380...480 V three phase LXM15MD28N4 400 V three phase LXM15MD28N4 480 V three phase LXM15MD40N4 400 V three phase LXM15MD40N4 480 V three phase LXM32.D30N4 400 V three phase LXM32.D30N4 480 V three phase
Shaft end	Keyed
IP Degree of Protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn x 4096 turns
Holding brake	Without
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Complementary

Range Compatibility	Lexium 05 Lexium 15 Lexium 32
supply voltage max	480 V
Phase	Three phase
Continuous stall current	6.6 A
maximum continuous power	3.14 W
Maximum current Irms	28.3 A LXM15LD21M3 28.3 A LXM15LD28M3 28.3 A LXM15LD17N4 28.3 A LXM15MD28N4 28.3 A LXM15MD40N4 28.3 A LXM05AD28M2 28.3 A LXM05AD42M3X 28.3 A LXM05AD34N4 28.3 A LXM05BD28M2 28.3 A LXM05BD42M3X 28.3 A LXM05BD34N4 28.3 A LXM05CD28M2 28.3 A LXM05CD42M3X 28.3 A LXM05CD34N4 28.3 A LXM32.D30N4
Maximum permanent current	28.3 A
Switching frequency	8 kHz
Second shaft	Without second shaft end
Shaft diameter	0.7 in (19 mm)
Shaft length	1.6 in (40 mm)
Key width	1.2 in (30 mm)
Feedback type	Multiturn SinCos Hiperface
Motor flange size	3.9 in (100 mm)

Number of motor stacks	3
Torque constant	1.22 N.m/A 248.0000000000 °F (120 °C)
Back emf constant	77 V/krpm 248.0000000000 °F (120 °C)
Number of motor poles	8
Rotor inertia	3.22 kg.cm²
Stator resistance	1.43 Ohm 68.0000000000 °F (20 °C)
Stator inductance	8.8 mH 68.0000000000 °F (20 °C)
Stator electrical time constant	6.15 ms 68.0000000000 °F (20 °C)
Maximum radial force Fr	1050 N 1000 rpm 660 N 4000 rpm 730 N 3000 rpm 830 N 2000 rpm
Maximum axial force Fa	0.2 x Fr
Type of cooling	Natural convection
Length	9.5 in (240.5 mm)
Centring collar diameter	3.7 in (95 mm)
Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (9 mm)
Circle diameter of the mounting holes	4.5 in (115 mm)
Net Weight	16.3 lb(US) (7.4 kg)

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3389118140349
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.80 in (22.35 cm)
Package 1 Width	7.6 in (19.3 cm)
Package 1 Length	15.90 in (40.39 cm)
Package 1 Weight	18.58 lb(US) (8.43 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	


Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Dimensions Drawings

Servo Motors Dimensions

Example with Straight Connectors



- a: Power supply for servo motor brake
b: Power supply for servo motor encoder
(1) M4 screw
(2) Shaft end, keyed slot (optional)

Dimensions in mm

Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2								
39.5	25.5	39.5	39.5	241	272	40	30	6 N9	3.5 ^{+0.1} ₀	19 k6	M6 x 16

Dimensions in in.


Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2								
1.55	1.00	1.55	1.55	9.48	10.70	1.57	1.18	0.24 N9	0.14 ^{+0.1} ₀	0.75 k6	M6 x 0.63

Performance Curves

400 V 3-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D30N4 servo drive




- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque

480 V 3-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D30N4 servo drive



- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque