

BSH1004P31F2A

AC servo motor BSH, Lexium 05, 9.31N.m,
1500rpm, keyed shaft, with brake, IP65





Main

Device short name	BSH
Product or Component Type	Servo motor
Maximum mechanical speed	6000 rpm
Continuous stall torque	<p>70.8 Lbf.In (8 N.m) LXM32.D30N4 10 A, 400 V, three phase</p> <p>70.8 Lbf.In (8 N.m) LXM32.D30N4 10 A, 480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD40N4, 400 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD40N4, 480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD28M3, 230 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD28N4, 230 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD28N4, 400 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD28N4, 480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM15MD40N4, 230 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05AD34N4, 380...480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05AD42M3X, 200...240 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05AD57N4, 380...480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05BD34N4, 380...480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05BD42M3X, 200...240 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05BD57N4, 380...480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05CD34N4, 380...480 V, three phase</p> <p>82.40 Lbf.In (9.31 N.m) LXM05CD42M3X, 200...240 V, three phase</p> <p>82.40 lbf.in (9.31 N.m) LXM05CD57N4, 380...480 V, three phase</p>

Peak stall torque	335.4 Lbf.In (37.9 N.m) LXM32.D30N4 10 A, 400 V, three phase	
	335.4 Lbf.In (37.9 N.m) LXM32.D30N4 10 A, 480 V, three phase	
	227.5 Lbf.In (25.7 N.m) LXM15MD28M3, 230 V, three phase	
	227.5 Lbf.In (25.7 N.m) LXM15MD28N4, 230 V, three phase	
	227.5 Lbf.In (25.7 N.m) LXM15MD28N4, 400 V, three phase	
	227.5 Lbf.In (25.7 N.m) LXM15MD28N4, 480 V, three phase	
	299.42 Lbf.In (33.83 N.m) LXM15MD40N4, 230 V, three phase	
	299.42 Lbf.In (33.83 N.m) LXM15MD40N4, 400 V, three phase	
	299.42 Lbf.In (33.83 N.m) LXM15MD40N4, 480 V, three phase	
	207.73 Lbf.In (23.47 N.m) LXM05AD34N4, 380...480 V, three phase	
	316.0 Lbf.In (35.7 N.m) LXM05AD42M3X, 200...240 V, three phase	
	316.0 Lbf.In (35.7 N.m) LXM05AD57N4, 380...480 V, three phase	
	207.73 Lbf.In (23.47 N.m) LXM05BD34N4, 380...480 V, three phase	
	316.0 Lbf.In (35.7 N.m) LXM05BD42M3X, 200...240 V, three phase	
	316.0 Lbf.In (35.7 N.m) LXM05BD57N4, 380...480 V, three phase	
	207.73 Lbf.In (23.47 N.m) LXM05CD34N4, 380...480 V, three phase	
	316.0 Lbf.In (35.7 N.m) LXM05CD42M3X, 200...240 V, three phase	
	316.0 lbf.in (35.7 N.m) LXM05CD57N4, 380...480 V, three phase	
	Nominal output power	2600 W LXM32.D30N4 10 A, 480 V, three phase
		2100 W LXM32.D30N4 10 A, 400 V, three phase
		1300 W LXM05AD42M3X, 200...240 V, three phase
		1300 W LXM05BD42M3X, 200...240 V, three phase
		1300 W LXM05CD42M3X, 200...240 V, three phase
		1300 W LXM15MD28M3, 230 V, three phase
1300 W LXM15MD28N4, 230 V, three phase		
1300 W LXM15MD40N4, 230 V, three phase		
2200 W LXM05AD34N4, 380...480 V, three phase		
2200 W LXM05AD57N4, 380...480 V, three phase		
2200 W LXM05BD34N4, 380...480 V, three phase		
2200 W LXM05BD57N4, 380...480 V, three phase		
2200 W LXM05CD34N4, 380...480 V, three phase		
2200 W LXM05CD57N4, 380...480 V, three phase		
2200 W LXM15MD28N4, 400 V, three phase		
2300 W LXM15MD40N4, 400 V, three phase		
2400 W LXM15MD40N4, 480 V, three phase		
2700 W LXM15MD28N4, 480 V, three phase		

Nominal torque	<p>73.5 Lbf.In (8.3 N.m) LXM32.D30N4 10 A, 400 V, three phase</p> <p>73.5 Lbf.In (8.3 N.m) LXM32.D30N4 10 A, 480 V, three phase</p> <p>57.5 Lbf.In (6.5 N.m) LXM15MD28N4, 480 V, three phase</p> <p>59.21 Lbf.In (6.69 N.m) LXM15MD40N4, 480 V, three phase</p> <p>62.0 Lbf.In (7 N.m) LXM15MD28N4, 400 V, three phase</p> <p>62.8 Lbf.In (7.1 N.m) LXM05AD34N4, 380...480 V, three phase</p> <p>62.8 Lbf.In (7.1 N.m) LXM05AD57N4, 380...480 V, three phase</p> <p>62.8 Lbf.In (7.1 N.m) LXM05BD34N4, 380...480 V, three phase</p> <p>62.8 Lbf.In (7.1 N.m) LXM05BD57N4, 380...480 V, three phase</p> <p>62.8 Lbf.In (7.1 N.m) LXM05CD34N4, 380...480 V, three phase</p> <p>62.8 Lbf.In (7.1 N.m) LXM05CD57N4, 380...480 V, three phase</p> <p>63.46 Lbf.In (7.17 N.m) LXM15MD40N4, 400 V, three phase</p> <p>72.40 Lbf.In (8.18 N.m) LXM15MD40N4, 230 V, three phase</p> <p>72.75 Lbf.In (8.22 N.m) LXM05AD42M3X, 200...240 V, three phase</p> <p>72.75 Lbf.In (8.22 N.m) LXM05BD42M3X, 200...240 V, three phase</p> <p>72.75 Lbf.In (8.22 N.m) LXM05CD42M3X, 200...240 V, three phase</p> <p>72.75 Lbf.In (8.22 N.m) LXM15LD28M3, 230 V, three phase</p> <p>72.75 lbf.in (8.22 N.m) LXM15MD28N4, 230 V, three phase</p>
Nominal speed	<p>2500 rpm LXM32.D30N4 10 A, 400 V, three phase</p> <p>3000 rpm LXM32.D30N4 10 A, 480 V, three phase</p> <p>1500 rpm LXM05AD42M3X, 200...240 V, three phase</p> <p>1500 rpm LXM05BD42M3X, 200...240 V, three phase</p> <p>1500 rpm LXM05CD42M3X, 200...240 V, three phase</p> <p>3000 rpm LXM05AD34N4, 380...480 V, three phase</p> <p>3000 rpm LXM05BD34N4, 380...480 V, three phase</p> <p>3000 rpm LXM05CD34N4, 380...480 V, three phase</p> <p>1500 rpm LXM15MD28M3, 230 V, three phase</p> <p>1500 rpm LXM15MD28N4, 230 V, three phase</p> <p>1500 rpm LXM15MD40N4, 230 V, three phase</p> <p>3000 rpm LXM05AD57N4, 380...480 V, three phase</p> <p>3000 rpm LXM05BD57N4, 380...480 V, three phase</p> <p>3000 rpm LXM05CD57N4, 380...480 V, three phase</p> <p>3000 rpm LXM15MD28N4, 400 V, three phase</p> <p>3000 rpm LXM15MD40N4, 400 V, three phase</p> <p>3500 rpm LXM15MD40N4, 480 V, three phase</p> <p>4000 rpm LXM15MD28N4, 480 V, three phase</p>
Product compatibility	<p>LXM05AD42M3X 200...240 V three phase</p> <p>LXM05BD42M3X 200...240 V three phase</p> <p>LXM05CD42M3X 200...240 V three phase</p> <p>LXM05AD34N4 380...480 V three phase</p> <p>LXM05BD34N4 380...480 V three phase</p> <p>LXM05CD34N4 380...480 V three phase</p> <p>LXM15MD28N4 400 V three phase</p> <p>LXM15MD28N4 480 V three phase</p> <p>LXM15MD40N4 400 V three phase</p> <p>LXM15MD40N4 480 V three phase</p> <p>LXM32.D30N4 400 V three phase</p> <p>LXM32.D30N4 480 V three phase</p> <p>LXM05AD57N4 380...480 V three phase</p> <p>LXM05BD57N4 380...480 V three phase</p> <p>LXM05CD57N4 380...480 V three phase</p> <p>LXM15MD28M3 230 V three phase</p> <p>LXM15MD28N4 230 V three phase</p> <p>LXM15MD40N4 230 V three phase</p>
Shaft end	Keyed
IP Degree of Protection	<p>IP65 standard</p> <p>IP67 with IP67 kit</p>

Speed feedback resolution	131072 points/turn
Holding brake	With
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Complementary

Range Compatibility	Lexium 15 Lexium 32 Lexium 05
Supply voltage max	480 V
Phase	Three phase
Continuous stall current	6.2 A
Maximum continuous power	3.64 W
Maximum current Irms	34.8 A LXM15LD28M3 34.8 A LXM15MD28N4 34.8 A LXM15MD40N4 32.3 A LXM05AD42M3X 32.3 A LXM05AD34N4 32.3 A LXM05AD57N4 32.3 A LXM05BD42M3X 32.3 A LXM05BD34N4 32.3 A LXM05BD57N4 32.3 A LXM05CD42M3X 32.3 A LXM05CD34N4 32.3 A LXM05CD57N4 30 A LXM32.D30N4
Maximum permanent current	32.3 A
Switching frequency	8 kHz
Second shaft	Without second shaft end
Shaft diameter	0.9 in (24 mm)
Shaft length	2.0 in (50 mm)
Key width	1.6 in (40 mm)
Feedback type	Single turn SinCos Hiperface
Holding torque	106.2 lbf.in (12 N.m) holding brake
Motor flange size	3.9 in (100 mm)
Number of motor stacks	4
Torque constant	1.62 N.m/A 248.0000000000 °F (120 °C)
Back emf constant	103 V/krpm 248.0000000000 °F (120 °C)
Number of motor poles	8
Rotor inertia	5.245 kg.cm ²
Stator resistance	1.81 Ohm 68.0000000000 °F (20 °C)
Stator inductance	11.8 mH 68.0000000000 °F (20 °C)
Stator electrical time constant	6.52 ms 68.0000000000 °F (20 °C)
Maximum radial force Fr	1070 N 1000 rpm 740 N 3000 rpm 850 N 2000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	17 W
Type of cooling	Natural convection
Length	12.1 in (307.5 mm)
Centring collar diameter	3.7 in (95 mm)
Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (9 mm)
Circle diameter of the mounting holes	4.5 in (115 mm)
Net Weight	21.8 lb(US) (9.9 kg)

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3389118140639
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 in (18.3 cm)
Package 1 Width	6.4 in (16.3 cm)
Package 1 Length	19.4 in (49.2 cm)
Package 1 Weight	17.97 lb(US) (8.15 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes


Contractual warranty

Warranty	18 months
----------	-----------

400 V 3-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32-D30N4 servo drive



X Speed in rpm

Y Torque in Nm


1 Peak torque

2 Continuous torque

480 V 3-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32-D30N4 servo drive



X Speed in rpm

Y Torque in Nm

1 Peak torque

2 Continuous torque