


BSH1403P21F2A

AC servo motor BSH, Lexium, 22.2N.m,
1500rpm, untapped shaft, with brake, IP65





Main

Product or Component Type	Servo motor
Device short name	BSH
Maximum mechanical speed	4000 rpm
Continuous stall torque	224.8 Lbf.In (25.4 N.m) LXM05AD57N4, 380...480 V, three phase 224.8 Lbf.In (25.4 N.m) LXM05BD57N4, 380...480 V, three phase 224.8 Lbf.In (25.4 N.m) LXM05CD57N4, 380...480 V, three phase 196.5 Lbf.In (22.2 N.m) LXM15MD40N4, 230 V, three phase 196.5 Lbf.In (22.2 N.m) LXM15MD40N4, 400 V, three phase 196.5 Lbf.In (22.2 N.m) LXM15MD40N4, 480 V, three phase 246.05 Lbf.In (27.8 N.m) LXM15MD56N4, 230 V, three phase 246.05 Lbf.In (27.8 N.m) LXM15MD56N4, 400 V, three phase 246.05 lbf.in (27.8 N.m) LXM15MD56N4, 480 V, three phase
Peak stall torque	368.2 Lbf.In (41.6 N.m) LXM15MD40N4, 230 V, three phase 368.2 Lbf.In (41.6 N.m) LXM15MD40N4, 400 V, three phase 368.2 Lbf.In (41.6 N.m) LXM15MD40N4, 480 V, three phase 507.1 Lbf.In (57.3 N.m) LXM15MD56N4, 230 V, three phase 507.1 Lbf.In (57.3 N.m) LXM15MD56N4, 400 V, three phase 507.1 Lbf.In (57.3 N.m) LXM15MD56N4, 480 V, three phase 507.32 Lbf.In (57.32 N.m) LXM05AD57N4, 380...480 V, three phase 507.32 Lbf.In (57.32 N.m) LXM05BD57N4, 380...480 V, three phase 507.32 lbf.in (57.32 N.m) LXM05CD57N4, 380...480 V, three phase
Nominal output power	3400 W LXM15MD56N4, 480 V, three phase 3000 W LXM15MD40N4, 230 V, three phase 3000 W LXM15MD56N4, 230 V, three phase 3400 W LXM15MD40N4, 480 V, three phase 3900 W LXM05AD57N4, 380...480 V, three phase 3900 W LXM05BD57N4, 380...480 V, three phase 3900 W LXM05CD57N4, 380...480 V, three phase 3900 W LXM15MD40N4, 400 V, three phase 3900 W LXM15MD56N4, 400 V, three phase
Nominal torque	109.7 Lbf.In (12.4 N.m) LXM15MD40N4, 400 V, three phase 109.7 Lbf.In (12.4 N.m) LXM15MD56N4, 400 V, three phase 110.01 Lbf.In (12.43 N.m) LXM05AD57N4, 380...480 V, three phase 110.01 Lbf.In (12.43 N.m) LXM05BD57N4, 380...480 V, three phase 110.01 Lbf.In (12.43 N.m) LXM05CD57N4, 380...480 V, three phase 166.4 Lbf.In (18.8 N.m) LXM15MD40N4, 230 V, three phase 166.4 Lbf.In (18.8 N.m) LXM15MD56N4, 230 V, three phase 71.7 Lbf.In (8.1 N.m) LXM15MD40N4, 480 V, three phase 71.7 lbf.in (8.1 N.m) LXM15MD56N4, 480 V, three phase

Nominal speed	1500 rpm LXM15MD40N4, 230 V, three phase 3000 rpm LXM05AD57N4, 380...480 V, three phase 3000 rpm LXM05BD57N4, 380...480 V, three phase 3000 rpm LXM05CD57N4, 380...480 V, three phase 3000 rpm LXM15MD40N4, 400 V, three phase 1500 rpm LXM15MD56N4, 230 V, three phase 3000 rpm LXM15MD56N4, 400 V, three phase 4000 rpm LXM15MD40N4, 480 V, three phase 4000 rpm LXM15MD56N4, 480 V, three phase
Product compatibility	LXM15MD40N4 400 V three phase LXM15MD40N4 480 V three phase LXM05AD57N4 380...480 V three phase LXM05BD57N4 380...480 V three phase LXM05CD57N4 380...480 V three phase LXM15MD40N4 230 V three phase LXM15MD56N4 230 V three phase LXM15MD56N4 400 V three phase LXM15MD56N4 480 V three phase
Shaft end	Untapped
IP Degree of Protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn
Holding brake	With
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Complementary

Range Compatibility	Lexium 05 Lexium 15
Supply voltage max	480 V
Phase	Three phase
Continuous stall current	17.6 A
Maximum continuous power	3.3 W
Maximum current Irms	61 A LXM15MD40N4 61 A LXM15MD56N4 61 A LXM05AD57N4 61 A LXM05BD57N4 61 A LXM05CD57N4
Maximum permanent current	61 A
Switching frequency	4 kHz
Second shaft	Without second shaft end
Shaft diameter	0.9 in (24 mm)
Shaft length	2.0 in (50 mm)
Feedback type	Single turn SinCos Hiperface
Holding torque	318.6 lbf.in (36 N.m) holding brake
Motor flange size	5.5 in (140 mm)
Number of motor stacks	3
Torque constant	1.58 N.m/A 248.0000000000 °F (120 °C)
Back emf constant	105 V/krpm 248.0000000000 °F (120 °C)
Number of motor poles	10
Rotor inertia	23.44 kg.cm ²
Stator resistance	0.4 Ohm 68.0000000000 °F (20 °C)
Stator inductance	5.1 mH 68.0000000000 °F (20 °C)
Stator electrical time constant	12.75 ms 68.0000000000 °F (20 °C)
Maximum radial force Fr	1780 N 3000 rpm 2030 N 2000 rpm 2560 N 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	26 W
Type of cooling	Natural convection
Length	14.4 in (365.5 mm)
Centring collar diameter	5.1 in (130 mm)

Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (11 mm)
Circle diameter of the mounting holes	6.5 in (165 mm)
Net Weight	50.7 lb(US) (23 kg)

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3389118142794
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.630 in (27.000 cm)
Package 1 Width	10.630 in (27.000 cm)
Package 1 Length	21.417 in (54.400 cm)
Package 1 Weight	37.02 lb(US) (16.790 kg)
Unit Type of Package 2	P06
Number of Units in Package 2	3
Package 2 Height	30.315 in (77.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	183.26 lb(US) (83.125 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------