Product data sheet

Specifications





Control relay, TeSys K, 3 NO + 1 NC, It or eq to 690V, 110VAC coil

CA2KN313F7

() Discontinued on: Jul 12, 2021

() Discontinued

Main

TeSys	
TeSys CAK	
Control relay	
CA2K	
Control circuit	
AC-15 DC-13	
3 NO + 1 NC	
<= 690 V <= 400 Hz	
AC 50/60 Hz	
110 V AC 50/60 Hz	
-	

Complementary

· · · · · · · · · · · · · · · · · ·		
[Ith] conventional free air thermal current	10 A (at 122 °F (50 °C))	
Irms rated making capacity	110 A IEC 60947	
Associated fuse rating	10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660	
[Ui] rated insulation voltage	690 V IEC 60947 750 V VDE 0110 group C 690 V BS 5424 600 V CSA C22.2 No 14	
Mounting Support	Plate Rail	
Connections - terminals	spring terminals 1 0.0010.002 in ² (0.751.5 mm ²)solid spring terminals 1 0.0010.002 in ² (0.751.5 mm ²)flexible without cable end	
Control circuit voltage limits	Drop-out: 0.20.75 Uc (at <122 °F (50 °C)) Operational: 0.81.15 Uc (at <122 °F (50 °C))	
Operating time	1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing 1525 ms coil de-energisation and NC closing 515 ms coil energisation and NC opening	
Mechanical durability	10 Mcycles	
Maximum operating rate	10000 cyc/h	
Immunity to microbreaks	2 ms	
Inrush power in VA	30 VA (at 68 °F (20 °C))	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Hold-in power consumption in VA	4.5 VA (at 68 °F (20 °C))	
Heat dissipation	1.3 W	
Minimum switching voltage	17 V	
Minimum switching current	5 mA	
Non overlap distance	0.02 in (0.5 mm)	
Insulation resistance	> 10 MOhm	
Height	2.3 in (58 mm)	
Width	1.8 in (45 mm)	
Depth	2.2 in (57 mm)	
Net Weight	0.40 lb(US) (0.18 kg)	

Environment

Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1	
Product Certifications	CB Scheme CCC UL CSA EAC CE UKCA	
Protective treatment	TC IEC 60068	
Ambient Air Temperature for Operation	-13122 °F (-2550 °C)	
Ambient Air Temperature for Storage	-58176 °F (-5080 °C)	
Operating altitude	tude 6561.68 ft (2000 m) without derating	
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	
Mechanical robustness	Vibrations contactor open2 Gn, 5300 Hz IEC 60068-2-6 Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6 Shocks contactor open10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed15 Gn for 11 ms IEC 60068-2-27	

Ordering and shipping details

Category	22371-RELAYS, CONTROL	
Discount Schedule	112	
GTIN	3389110241662	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.9 in (4.8 cm)	
Package 1 Width	2.6 in (6.5 cm)	
Package 1 Length	2.4 in (6.2 cm)	

Package 1 Weight

7.3 oz (207 g)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov