Product datasheet

Specification





TeSys K control relay - 3 NO + 1 NC - <= 690 V - 220...230 V AC coil

CA2KN31M7

Main

Range	TeSys	
Product name	TeSys CAK	
product or component type	Control relay	
Device short name	CA2K	
contactor application	Control circuit	
Utilisation category	AC-15 DC-13	
Pole contact composition	3 NO + 1 NC	
[Ue] rated operational voltage	<= 690 V <= 400 Hz	
Control circuit type	AC at 50/60 Hz	
[Uc] control circuit voltage	220230 V AC 50/60 Hz	

Complementary

Odinpicinental y		
[Ith] conventional free air thermal current	10 A (at 50 °C)	
Irms rated making capacity	110 A conforming to IEC 60947	
Associated fuse rating	10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660	
[Ui] rated insulation voltage	690 V conforming to IEC 60947 750 V conforming to VDE 0110 group C 690 V conforming to BS 5424 600 V conforming to CSA C22.2 No 14	
mounting support	Plate Rail	
Connections - terminals	Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.341.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible without cable end	
Tightening torque	1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 26 mm 1.3 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
Control circuit voltage limits	Prol circuit voltage limits Drop-out: 0.20.75 Uc (at <50 °C) Operational: 0.81.15 Uc (at <50 °C)	
Operating time	1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing 1525 ms coil de-energisation and NC closing 515 ms coil energisation and NC opening	
Mechanical durability	10 Mcycles	

02-Jul-2024 Life Is On Schneider

Maximum operating rate	10000 cyc/h	
Immunity to microbreaks	2 ms	
Inrush power in VA	30 VA (at 20 °C)	
Hold-in power consumption in VA	4.5 VA (at 20 °C)	
Heat dissipation	1.3 W	
Minimum switching voltage	17 V	
Minimum switching current	5 mA	
Non overlap distance	0.5 mm	
Insulation resistance	> 10 MOhm	
Height	58 mm	
Width	45 mm	
Depth	57 mm	
net weight	0.18 kg	

Environment

Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1	
Product certifications	CB Scheme CCC UL CSA EAC CE	
IP degree of protection	IP2X	
Protective treatment	TC conforming to IEC 60068	
Ambient air temperature for operation	-2550 °C	
Ambient air temperature for storage	-5080 °C	
Operating altitude	2000 m without derating	
Flame retardance	Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	
Mechanical robustness	Vibrations contactor open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	5.000 cm
Package 1 Length	6.500 cm
Package 1 Weight	177.400 g
Unit Type of Package 2	P06

Number of Units in Package 2	50
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	153.880 kg
Unit Type of Package 3	S02
Number of Units in Package 3	50
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	9.118 kg

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

REACh Declaration
Compliant
EU RoHS Declaration
China RoHS declaration
Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
End of Life Information

02-Jul-2024