## **Product data sheet**

Specifications





# TeSys SK control relay - 1 NO + 1 NC - <= 690 V - 400 V AC coil

CA2SK11V7

Discontinued on: May 19, 2023

#### ! Discontinued

#### Main

Range	TeSys	
Product Name	TeSys CASK	
Product Or Component Type	Control relay	
Device Short Name	CA2SK	
Contactor Application	Control circuit	
Utilisation Category	AC-15 DC-13	
Pole Contact Composition	1 NO + 1 NC	
[Ue] Rated Operational Voltage	<= 690 V <= 400 Hz	
Control Circuit Type	AC 50/60 Hz	
[Uc] Control Circuit Voltage	400 V AC 50/60 Hz	

## Complementary

10 A (at 131 °F (55 °C))
10 A gL conforming to VDE 0660
10 A gL conforming to IEC 60947
690 V IEC 60947
690 V VDE 0110 group C
690 V BS 5424
690 V UL 508
690 V CSA C22.2 No 14
Plate
Rail
screw clamp terminals 1 0.000.01 in² (1.56 mm²)solid
screw clamp terminals 2 0.000.01 in <sup>2</sup> (1.54 mm <sup>2</sup> )solid
screw clamp terminals 1 0.000.01 in² (0.56 mm²)flexible without cable end
screw clamp terminals 1 0.000.01 in² (0.356 mm²)flexible with cable end
screw clamp terminals 2 0.000.00 in <sup>2</sup> (0.351.5 mm <sup>2</sup> )flexible with cable end
screw clamp terminals 2 0.000.00 in² (0.352.5 mm²)flexible without cable end
7.08 lbf.in (0.8 N.m) screw clamp terminals pozidriv No 1
Drop-out: 0.20.75 Uc (at <122 °F (50 °C))
Operational: 0.851.1 Uc (at <122 °F (50 °C))
68 ms coil de-energisation and NO opening
714 ms coil energisation and NO closing
810 ms coil de-energisation and NC closing
816 ms coil energisation and NC opening
10 Mcycles
1200 cyc/h

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Inrush Power In Va	16 VA (at 68 °F (20 °C))
Hold-In Power Consumption In Va	4.2 VA (at 68 °F (20 °C))
Heat Dissipation	1.4 W
Height	2.20 in (56 mm)
Width	1.06 in (27 mm)
Depth	2.19 in (55.5 mm)
Net Weight	0.29 lb(US) (0.132 kg)

## **Environment**

Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1	
Product Certifications	CB Scheme cULus EAC CE UKCA	
Ip Degree Of Protection	IP2X	
Protective Treatment	TC IEC 60068	
Ambient Air Temperature For Operation	-4122 °F (-2050 °C)	
Ambient Air Temperature For Storage	-58158 °F (-5070 °C)	
Operating Altitude	6561.68 ft (2000 m) without derating	

## Ordering and shipping details

Category	22371-RELAYS, CONTROL	
Discount Schedule	112	
Gtin	3389110564136	
Returnability	No	
Country Of Origin	CZ	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.64 in (6.7 cm)
Package 1 Width	2.32 in (5.9 cm)
Package 1 Length	1.30 in (3.3 cm)
Package 1 Weight	4.66 oz (132 g)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information