# **Product data sheet**

Specifications





# Control relay, TeSys K, 2 NO + 2 NC, It or eq to 690V, 125VDC standard coil

CA3KN22GD

Product availability: Stock - Normally stocked in distribution

Price\*: 50.20 USD

### Main

Range	TeSys	
Product name	TeSys CAK	
Product or Component Type	Control relay	
Device short name	CA3K	
contactor application	Control circuit	
Utilisation category	AC-15 DC-13	
Pole contact composition	2 NO + 2 NC	
[Ue] rated operational voltage	<= 690 V <= 400 Hz	
Control circuit type	DC standard	
[Uc] control circuit voltage	125 V DC	

## Complementary

[Ith] conventional free air thermal	10 A (at 122 °F (50 °C))
current	(22
Irms rated making capacity	110 A IEC 60947
Associated fuse rating	10 A gG conforming to IEC 60947
	10 A gG conforming to VDE 0660
[Ui] rated insulation voltage	690 V IEC 60947
	750 V VDE 0110 group C
	690 V BS 5424
	600 V CSA C22.2 No 14
Mounting Support	Plate
	Rail
Connections - terminals	screw clamp terminals 1 0.0020.006 in² (1.54 mm²)solid
	screw clamp terminals 2 0.0020.006 in² (1.54 mm²)solid
	screw clamp terminals 1 0.0010.006 in² (0.754 mm²)flexible with cable end
	screw clamp terminals 2 0.0010.006 in² (0.754 mm²)flexible without cable end
	screw clamp terminals 1 0.00050.002 in <sup>2</sup> (0.341.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 2 0.00050.002 in <sup>2</sup> (0.341.5 mm <sup>2</sup> )flexible without cable end
	sciew clamp terminals 2 0.00050.002 iii (0.341.5 mini )iiexible without cable end
Tightening torque	11.5 lbf.in (1.3 N.m) screw clamp terminals flat Ø 6 mm
	11.5 lbf.in (1.3 N.m) screw clamp terminals Philips No 2 0.2 in (6 mm)
	11.5 lbf.in (1.3 N.m) screw clamp terminals pozidriv No 2
Control circuit voltage limits	Operational: 0.81.15 Uc (at <122 °F (50 °C))
	Drop-out: 0.10.75 Uc (at <122 °F (50 °C))
Operating time	10 ms coil de-energisation and NO opening
	3040 ms coil energisation and NO closing
	15 ms coil de-energisation and NC closing
	2535 ms coil energisation and NC opening

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mechanical durability	20 Mcycles	
Maximum operating rate	10000 cyc/h	
Immunity to microbreaks	2 ms	
Inrush power in W	3 W 68 °F (20 °C))	
Hold-in power consumption in W	3 W 68 °F (20 °C)	
Heat dissipation	3 W	
Minimum switching voltage	17 V	
Minimum switching current	5 mA	
Non overlap distance	0.02 in (0.5 mm)	
Insulation resistance	> 10 MOhm	
Height	2.3 in (58 mm)	
Width	1.8 in (45 mm)	
Depth	2.2 in (57 mm)	
Net Weight	0.496 lb(US) (0.225 kg)	

## **Environment**

Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1	
Product Certifications	CB Scheme CCC UL CSA EAC CE	
IP degree of protection	IP2X	
Protective treatment	TC IEC 60068	
Ambient Air Temperature for Operation	-13122 °F (-2550 °C)	
Ambient Air Temperature for Storage	-58176 °F (-5080 °C)	
Operating altitude	6561.68 ft (2000 m) without derating	
Flame retardance	ne retardance  V1 conforming to UL 94  Requirement 2 conforming to NF F 16-101  Requirement 2 conforming to NF F 16-102	
Mechanical robustness	Vibrations contactor open2 Gn, 5300 Hz IEC 60068-2-6 Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6 Shocks contactor open10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed15 Gn for 11 ms IEC 60068-2-27	

## Ordering and shipping details

Category	US10I1222371	
Discount Schedule	0112	
GTIN	3389110483901	
Returnability	No	
Country of origin	US	

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.9 in (4.8 cm)	
Package 1 Width	2.4 in (6.2 cm)	
Package 1 Length	2.6 in (6.5 cm)	
Package 1 Weight	7.6 oz (215 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	40	
Package 2 Height	5.9 in (15 cm)	
Package 2 Width	11.8 in (30 cm)	
Package 2 Length	15.7 in (40 cm)	
Package 2 Weight	19.875 lb(US) (9.015 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	320	
Package 3 Height	31.5 in (80 cm)	
Package 3 Width	31.5 in (80 cm)	
Package 3 Length	23.6 in (60 cm)	
Package 3 Weight	178.44 lb(US) (80.94 kg)	

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Aug 9, 2024