



PRODUCT-DETAILS

CA5-11/11M

CA5-11/11M Auxiliary Contact Block



General Information	
Extended Product Type	CA5-11/11M
Product ID	1SBN010040R1118
EAN	3471522121165
Catalog Description	CA5-11/11M Auxiliary Contact Block
Long Description	CA5-11/11M is a 4-pole front mounted auxiliary contact block equipped with screw terminals. CA5-...M version offers terminal assortment matching the marking of 3-pole A9..16-30-10 contactors. CA5-11/11M is available with 1 N.O. and 1 N.C. instantaneous contacts, 1 N.O. leading contact and 1 N.C. lagging contact for standard industrial environments.

Ordering	
Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

Popular Downloads	
Data Sheet, Technical	1SBC100214C0202

Information	
Instructions and Manuals	1SBC101012M5501
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	43 mm
Product Net Depth / Length	39 mm
Product Net Height	47 mm
Product Net Weight	0.06 kg

Technical

Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Number of Poles	4P
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Maximum Electrical Switching Frequency	1200 cycles per hour
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Minimum Switching Capacity	A9 ... A40-30-10 17 / 5 VLT4K
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Terminal Type	Screw Terminals
Suitable For	A9 A12 A16 A26 A30 A40 AL9

	AL9Z
	AL12
	AL12Z
	AL16
	AL16Z
	AL26
	AL30
	AL40
	TAL9
	TAL12
	TAL16
	TAL26
	TAL30
	TAL40
	UA16
	UA26
	UA30
Product Name	Auxiliary Contact Block
Remarks	100

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_SE_62119A1
CCC Certificate	CCC_2015010304800518
CQC Certificate	CQC2015010304800518 CQC2004010305133985
Declaration of Conformity - CCC	2020980304001627 2020980305001185
Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001

Container Information

Package Level 1 Units	box 2 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Height	43 mm
Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522121165
Package Level 2 Units	box 32 piece

Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	1.92 kg
Package Level 3 Units	2880 piece

Classifications

Object Classification Code	K
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

