CA5-31MRT 1/4



PRODUCT-DETAILS

CA5-31MRT

CA5-31MRT Auxiliary Contact Block



General Information	
Extended Product Type	CA5-31MRT
Product ID	1SBN010042R1131
EAN	3471522364616
Catalog Description	CA5-31MRT Auxiliary Contact Block
Long Description	CA5-31MRT is a 4-pole front mounted auxiliary contact block equipped with screw terminals for connection with ring tongue ferrules. CA5M version offers terminal assortment matching the marking of 3-pole TAL940-30-10RT contactors. CA5-31MRT is available with 3 N.O. and 1 N.C. instantaneous contacts for standard industrial environments.

Ordering	
Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

Popular Downloads	
Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and Manuals	1SBC101011M5501

CA5-31MRT 2/4

CAD Dimensional 2CDC001079B0201 Drawing **Dimensions** Product Net Width 43 mm Product Net Depth / 39 mm Length Product Net Height 47 mm **Product Net Weight** 0.06 kg Technical Number of Auxiliary 3 Contacts NO Number of Auxiliary 1 Contacts NC 4P Number of Poles Auxiliary Circuit 690 V Rated Operational Voltage Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz Rated Operational Current (500 V) 2 A AC-15 (I_e) (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A Rated Operational Current (24 V) 6 A / 144 W DC-13 (I_e) (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W Rated Short-time for 0.1 s 140 A for 1 s 100 A Withstand Current Low Voltage (I_{cw}) Rated Insulation Voltage acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V (U_i) Degree of Protection acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP10 **Terminal Type** Ring-Tongue Terminals Suitable For A9 A12 A16 A26 A30 A40 AL9 AL9Z AL12 AL12Z AL16 AL16Z AL26 AL30 AL40 TAL9 TAL12 TAL16 TAL26 TAL30 TAL40 **Auxiliary Contact Block** Product Name Material Compliance Conflict Minerals 9AKK108467A5658 Reporting Template (CMRT)

CA5-31MRT 3/4

REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations		
CB Certificate	CB_SE_62119A1	
CCC Certificate	CCC 2015010304800518	
CQC Certificate	CQC2015010304800518 CQC2004010305133985	
Declaration of Conformity - CCC	2020980304001627 2020980305001185	
Declaration of Conformity - CE	1SBD250809U1000	
Declaration of Conformity - UKCA	1SBD250826U1000	
EAC Certificate	EAC_RU C-FR ME77 B03391	
GOST Certificate	GOST_POCCFRME77B07175	
RINA Certificate	RINA ELE172319XG001	

Container Information	
Package Level 1 Units	2 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Height	43 mm
Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522364616
Package Level 2 Units	32 piece
Package Level 2 Gross Weight	1.92 kg
Package Level 3 Units	2880 piece

Classifications	
Object Classification Code	K
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

CA5-31MRT 4/4

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Contactors \rightarrow Block\ Contactors$

