

PRODUCT-DETAILS

## **CAL16-11C**

# CAL16-11C Auxiliary Contact Block



General Information	
Extended Product Type	CAL16-11C
Product ID	SK829002-C
EAN	7320500040294
Catalog Description	CAL16-11C Auxiliary Contact Block
Long Description	2 pole screw type left outer side mounted auxilliary contact block, instantaneous N.O.

Ordering	
7320500040294	
1 piece	
85369010	

Dimensions	
Product Net Width	12.5 mm
Product Net Height	68 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.05 kg

#### **Container Information**

Package Level 1 Units	bag 1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	18 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Gross Weight	0.06 kg
Package Level 1 EAN	7320500040294

### **Environmental**

B 116.61	E II EUD:
RoHS Status	Following EU Directive 2011/65/EU

Additional Information	
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-5-1, q = 40 °C 16 A
Connecting Terminals (delivered in open position)	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Minimum Switching Capacity	0.25 VA/ 12 V / 5 mA
Power Loss	at Rated Operating Conditions per Pole 0.2 W
Product Main Type	CAL16
Product Name	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x le AC-15
Rated Frequency (f)	Supply Circuit 50 60 Hz
Rated Insulation Voltage (Ui)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Making Capacity acc. to IEC 60947-5-1	10 x le AC-15
Rated Operational Current AC-15 (I <sub>e</sub> )	(220 / 240 V) 6 A (24 / 127 V) 6 A (380 / 440 V) 4 A (500 V) 1 A (690 V) 1 A
Rated Operational Current DC-13 (I <sub>e</sub> )	(125 V) 1.8 A (24 V) 6 A (250 V) 0.6 A (48 V) 6 A (72 V) 4 A
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 0.1 s 100 A for 1 s 50 A
Replaced Product ID (OLD)	SK829001-C
RoHS Date	1713
Suitable For	A-line
Suitable for Product Class	CONTACTORS

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	1SBC100122C0202
Declaration of Conformity - CE	2CMT2015-005448
Instructions and Manuals	5309660-30
RoHS Information	2CMT2016-006030

CAL16-11C 3

Classifications	
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
Object Classification Code	к
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

#### **Categories**

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Contactors\ \rightarrow\ Block\ Contactors\ Accessories$   $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Contactors\ \rightarrow\ Service$   $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Contactors\ \rightarrow\ Service\ \rightarrow\ Spares\ and\ Consumables$ 

