

PRODUCT-DETAILS

CB1-600G CB1-600G Buzzer



| General Information | | |
|--------------------------------------|--|-------------------|
| Extended Product Type | CB1-600G | |
| Product ID | 1SFA619600R6002 | |
| EAN | 7320500556764 | |
| Catalog Description | CB1-600G Buzzer | |
| Long Description | The CB1-600G Buzzer is: Compact - Buzzer - Continuous sound with continuous light - Green - Illuminated - 24 V This Buzzer is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance. | |
| Ordering | 10 - 1 | |
| Minimum Order Quantity | 10 piece | |
| Customs Tariff Number | 85369001 | |
| Popular Downloads | | |
| Data Sheet, Technical Information | 1SFC151007C02 | |
| Instructions and Manuals | 1SFC151011M0201 | |
| © 2025 ABB. All rights reserved. | 2025/01/16 Subject to chan | ge without notice |

| Dimensions | |
|-------------------------------|----------|
| Product Net Width | 0.03 m |
| Product Net Height | 0.03 m |
| Product Net Depth / Length | 0.055 m |
| Product Net Weight | 0.021 kg |

| Technical | |
|--------------------------------------|--|
| Ambient Air Temperature | Operation -25 +70 °C Storage -40 +85 °C |
| Color | Green |
| Illumination | Illuminated |
| Function | Continuous sound with continuous light |
| Enclosure Type NEMA | Type1 Type12 Type13 Type3R Type4X Type4X |
| Pollution Degree | 3 |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Operational Voltage | Supply Circuit 24 V AC/DC |
| Sound dB (A) | 80 dB |
| Connecting Capacity | Flexible with Ferrule 1 x 0.752.5 mm ² Flexible with Ferrule 2 x 0.752.5 mm ² Flexible with Insulated Ferrule 2 x 0.752.5 mm ² Flexible with Insulated Ferrule 2 x 0.752.5 mm ² Flexible 1 x 0.75 2.5 mm ² Flexible 2 x 0.75 2.5 mm ² Solid 1 x 0.752.5 mm ² Solid 2 x 0.752.5 mm ² |
| Connection Type | Screw Clamp |
| Terminal Type | Screw Terminals |
| Tightening Torque | 0.9 N·m |
| Wire Stripping Length | 8 mm |
| Technical UL/CSA | |
| Connecting Capacity <u>UL/CSA</u> | 1x 1814 AWG 2x 1814 AWG |
| Environmental | |
| | |
| Degree of Protection | Front IP66 Front IP67 Front IP69K Terminals IP20 |

| Material Compliance | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2022-006479 |
| RoHS Information | 2CMT2022-006498 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control | 2CMT2023-006523 |

© 2025 ABB. All rights reserved.

Subject to change without notice

| Act - TSCA | |
|----------------|--|
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

| CB Certificate | CQC_CN_CN50749 |
|-------------------------------------|---------------------|
| CQC Certificate | CQC2003010305054693 |
| cURus Certificate | UL_E496500-20171020 |
| Declaration of Conformity - CCC | 2020980305001187 |
| Declaration of Conformity - CE | 2CMT2015-00545 |
| Declaration of Conformity - UKCA | 2CMT2020-00612 |
| DNV GL Certificate | 9AKK107046A3749 |

| Container Information | |
|-----------------------------------|---------------|
| Package Level 1 Units | bag 10 piece |
| Package Level 1 Width | 0.05 m |
| Package Level 1 Depth / Length | 0.235 m |
| Package Level 1 Height | 0.125 m |
| Package Level 1 Gross Weight | 0.214 kg |
| Package Level 1 EAN | 7320500400944 |

| External Classifications and Standards | |
|--|-------------------------------|
| Object Classification Code | Р |
| ETIM 6 | EC001026 - Acoustic indicator |
| ETIM 7 | EC001026 - Acoustic indicator |
| ETIM 8 | EC001026 - Acoustic indicator |
| eClass | V11.0 : 27371214 |
| UNSPSC | 46171607 |
| IDEA Granular Category Code (IGCC) | 7389 >> Buzzers |
| E-Number (Finland) | 2313689 |
| E-Number (Sweden) | 3705036 |

Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Control Products} \rightarrow \text{Pilot Devices} \rightarrow \text{Compact Range} \rightarrow \text{CB Compact Buzzers}$

