

PRODUCT-DETAILS

CB1-611R

BUZZER CB1-611R



General Information

| | |
|-----------------------|---|
| Extended Product Type | CB1-611R |
| Product ID | 1SFA619600R6111 |
| EAN | 7320500556825 |
| Catalog Description | BUZZER CB1-611R |
| Long Description | Compact Buzzer - Pulsating sound with pulsating light - Red - Illuminated |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85369001 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02_ |
| Instructions and Manuals | 1SFC151011M0201 |

Dimensions

| | |
|---------------------|---------|
| Product Net Width | 0.03 m |
| Product Net Height | 0.03 m |
| Product Net Depth / | 0.055 m |

Length

| | |
|--------------------|----------|
| Product Net Weight | 0.021 kg |
|--------------------|----------|

Technical

| | |
|---------------------------|--|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -40 ... +85 °C |
| Color | Red |
| Illumination | Illuminated |
| Function | Pulsating sound with pulsating light |
| Degree of Protection | Front IP66 Front IP67 Front IP69K Terminals IP20 |
| Enclosure Type NEMA | Type1 Type12 Type13 Type3R Type4 Type4X |
| Pollution Degree | 3 |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Operational Voltage | Supply Circuit 110 ... 130 V AC |
| Sound dB (A) | 80 dB |
| Connecting Capacity | Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ² |
| Connection Type | Screw Clamp |
| Terminal Type | Screw Terminals |
| Tightening Torque | 0.9 N·m |
| Wire Stripping Length | 8 mm |

Technical UL/CSA

| | |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA | 2x 18...14 AWG |

Environmental

| | |
|------------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 635 4 |
| RoHS Information | 2CMT2015-005451 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |

Certificates and Declarations (Document Number)

| | |
|---------------------------------|---------------------|
| CB Certificate | CQC_CN_CN50749 |
| CCC Certificate | 2003010305054693_ |
| CQC Certificate | CQC2003010305054693 |
| cURus Certificate | UL_E496500-20171020 |
| Declaration of Conformity - CCC | 2020980305001187 |
| Declaration of | 2CMT2015-005451 |

Conformity - CE

| | |
|---------------------------|-----------------|
| DNV GL Certificate | 9AKK107046A3749 |
| Environmental Information | 1SAC200023H0002 |
| Instructions and Manuals | 1SFC151011M0201 |
| RoHS Information | 2CMT2015-005451 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | bag 10 piece |
| Package Level 1 Width | 0.05 m |
| Package Level 1 Depth / Length | 0.235 m |
| Package Level 1 Height | 0.125 m |
| Package Level 1 Gross Weight | 0.214 kg |
| Package Level 1 EAN | 7320500401194 |

Classifications

| | |
|----------------------------|-------------------------------|
| Object Classification Code | P |
| ETIM 6 | EC001026 - Acoustic indicator |
| ETIM 7 | EC001026 - Acoustic indicator |
| ETIM 8 | EC001026 - Acoustic indicator |
| eClass | V11.0 : 27371214 |
| UNSPSC | 39121500 |
| E-Number (Finland) | 2313701 |
| E-Number (Sweden) | 3705814 |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

