

## PRODUCT-DETAILS

# CE4K1-10R-02

## EMERGENCY STOP CE4K1-10R-02



### General Information

|                       |                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------|
| Extended Product Type | CE4K1-10R-02                                                                                       |
| Product ID            | 1SFA619552R1051                                                                                    |
| EAN                   | 7320500556733                                                                                      |
| Catalog Description   | EMERGENCY STOP CE4K1-10R-02                                                                        |
| Long Description      | Compact Emergency Stop - Key release - Mushroom 40mm - Red - Non-illuminated - Black plastic - 2NC |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number  | 85369001 |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals          | 1SFC151011M0201 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 0.04 m |
| Product Net Height | 0.04 m |

|                            |          |
|----------------------------|----------|
| Product Net Depth / Length | 0.103 m  |
| Product Net Weight         | 0.068 kg |

## Technical

|                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                             | Operation -25 ... +70 °C<br>Storage -40 ... +85 °C                                                                                                                                                                                                                                                                                                                                                               |
| Color                                               | Red                                                                                                                                                                                                                                                                                                                                                                                                              |
| Actuator Type                                       | Mushroom 40 mm                                                                                                                                                                                                                                                                                                                                                                                                   |
| Bezel Material                                      | n/a                                                                                                                                                                                                                                                                                                                                                                                                              |
| Illumination                                        | Non-illuminated                                                                                                                                                                                                                                                                                                                                                                                                  |
| Function                                            | Maintained                                                                                                                                                                                                                                                                                                                                                                                                       |
| Sub-Function                                        | Key release                                                                                                                                                                                                                                                                                                                                                                                                      |
| Key Code                                            | Key code 71                                                                                                                                                                                                                                                                                                                                                                                                      |
| Number of Auxiliary Contacts NC                     | 2                                                                                                                                                                                                                                                                                                                                                                                                                |
| Number of Auxiliary Contacts NO                     | 0                                                                                                                                                                                                                                                                                                                                                                                                                |
| Degree of Protection                                | Front IP66<br>Front IP67<br>Front IP69K<br>Terminals IP20                                                                                                                                                                                                                                                                                                                                                        |
| Enclosure Type NEMA                                 | Type1<br>Type12<br>Type13<br>Type3R<br>Type4<br>Type4X                                                                                                                                                                                                                                                                                                                                                           |
| Pollution Degree                                    | 3                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rated Insulation Voltage (U <sub>i</sub> )          | 300 V                                                                                                                                                                                                                                                                                                                                                                                                            |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 6 kV                                                                                                                                                                                                                                                                                                                                                                                                             |
| Rated Frequency (f)                                 | 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                       |
| Rated Operational Voltage                           | 24 ... 300 V                                                                                                                                                                                                                                                                                                                                                                                                     |
| Rated Operational Current DC-13 (I <sub>e</sub> )   | (24 V) 0.3 A<br>(125 V) 0.2 A                                                                                                                                                                                                                                                                                                                                                                                    |
| Rated Operational Current AC-15 (I <sub>e</sub> )   | (240 V) 1 A                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power Loss                                          | Maximum 5 W                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mechanical Durability                               | 0.5 million                                                                                                                                                                                                                                                                                                                                                                                                      |
| Connecting Capacity                                 | Flexible with Ferrule 1 x 0.5...1.5 mm <sup>2</sup><br>Flexible with Ferrule 2 x 0.5...1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1 x 0.5...1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2 x 0.5...1.5 mm <sup>2</sup><br>Flexible 1 x 0.5 ...1.5 mm <sup>2</sup><br>Flexible 2 x 0.5 ...1.5 mm <sup>2</sup><br>Solid 1 x 0.5...1.5 mm <sup>2</sup><br>Solid 2 x 0.5...1.5 mm <sup>2</sup> |
| Connection Type                                     | Screw Clamp                                                                                                                                                                                                                                                                                                                                                                                                      |
| Terminal Type                                       | Screw Terminals                                                                                                                                                                                                                                                                                                                                                                                                  |
| Tightening Torque                                   | 0.8 N·m                                                                                                                                                                                                                                                                                                                                                                                                          |
| Wire Stripping Length                               | 6 mm                                                                                                                                                                                                                                                                                                                                                                                                             |

## Technical UL/CSA

|                     |                |
|---------------------|----------------|
| Connecting Capacity | 1x 22...14 AWG |
| UL/CSA              | 2x 22...14 AWG |

## Environmental

|                  |                                                                        |
|------------------|------------------------------------------------------------------------|
| RoHS Status      | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date        | 0626 5                                                                 |
| RoHS Information | 2CMT2019-005802                                                        |
| WEEE Category    | 5. Small Equipment (No External Dimension More Than 50 cm)             |
| WEEE B2C / B2B   | Business To Business                                                   |

## Certificates and Declarations (Document Number)

|                                    |                             |
|------------------------------------|-----------------------------|
| CB Certificate                     | CN54150<br>CQC_CN_CN50749   |
| CCC Certificate                    | 2003010305054693_           |
| CQC Certificate                    | CQC2003010305054693         |
| cULus Certificate                  | UL_E496500-20171020         |
| Declaration of<br>Conformity - CCC | 2020980305001187            |
| Declaration of<br>Conformity - CE  | 2CMT2019-005802             |
| DNV GL Certificate                 | 9AKK107046A3749             |
| EAC Certificate                    | EAC RU C-CN.ME77.B.00537/19 |
| Environmental<br>Information       | 1SAC200072H0001             |
| Instructions and<br>Manuals        | 1SFC151011M0201             |
| RoHS Information                   | 2CMT2019-005802             |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | bag 1 piece   |
| Package Level 1 Width             | 0.09 m        |
| Package Level 1 Depth /<br>Length | 0.165 m       |
| Package Level 1 Height            | 0.04 m        |
| Package Level 1 Gross<br>Weight   | 0.07 kg       |
| Package Level 1 EAN               | 7320500308820 |

## Classifications

|                               |                                    |
|-------------------------------|------------------------------------|
| Object Classification<br>Code | S                                  |
| ETIM 6                        | EC002034 - Emergency stop complete |
| ETIM 7                        | EC002034 - Emergency stop complete |
| ETIM 8                        | EC002034 - Emergency stop complete |
| eClass                        | V11.0 : 27371244                   |
| UNSPSC                        | 39121545                           |
| E-Number (Finland)            | 2313548                            |
| E-Number (Norway)             | 4372820                            |
| E-Number (Sweden)             | 3711526                            |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

