



PRODUCT-DETAILS

CE5-01W0.1

CE5-01W0.1 Auxiliary Contact Block



General Information	
Extended Product Type	CE5-01W0.1
Product ID	1SBN010016R1001
EAN	3471522199164
Catalog Description	CE5-01W0.1 Auxiliary Contact Block
Long Description	CE5-01W0.1 is a 1-pole front mounted auxiliary contact block equipped with screw terminals and can be fitted on AF09(Z)...96, A9...75, AFC09...38, AL9...AE75, AX9...AX80 contactors and NF(C)(Z), N, NL, NX contactor relays. CE5-01W0.1 is used for the operation of auxiliary circuits and control circuits for severe industrial environments. CE5-01W0.1 is available with 1 N.C. including a built-in microswitch IP67, degree of protection (IP20 on terminals), defined for a 0.1 A AC-14 24-127 V 50/60 Hz / DC-12 24-110 V DC.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical Information	1SBC100214C0202
Instructions and Manuals	1SBC101013M5501
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	9.8 mm
Product Net Depth / Length	32.5 mm
Product Net Height	46.8 mm
Product Net Weight	0.02 kg

Technical

Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Number of Poles	1P
Standards	IEC/EN 60947-5-1
Rated Operational Voltage	Auxiliary Circuit 125 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I _e)	(24 / 127 V) 0.1 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 250 V
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP67
Tightening Torque	Auxiliary Circuit 1 N·m
Terminal Type	Screw Terminals
Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38 AF38Z AF40 AF52 AF65 AF80 AF96 AFC09 AFC12 AFC16 AFC26 AFC30 AFC38 NF22E NFZ22E NF31E

NFZ31E
NF40E
NFZ40E
NFC22E
NFC31E
NFC40E
A9
A12
A16
A26
A30
A40
A50
A63
A75
A95
A110
AL9
AL9Z
AL12
AL12Z
AL16
AL16Z
AL26
AL30
AL40
AE45
AE50
AE63
AE75
N22E
N31E
N40E
NL31E
NLZ31E
NL40E
NLZ40E
AX06
AX09
AX12
AX18
AX25
AX32
AX40
AX50
AX65
AX80
NX22E
NX31E
NX40E

Product Name

Auxiliary Contact Block

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_SE-94569
----------------	-------------

CQC Certificate	CQC2011010304466171
Declaration of Conformity - CCC	2020980304001286
Declaration of Conformity - CE	1SBD250817U1000
Declaration of Conformity - UKCA	1SBD250834U1000
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001

Container Information

Package Level 1 Units	blister 1 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Height	10 mm
Package Level 1 Gross Weight	0.02 kg
Package Level 1 EAN	3471522199164
Package Level 2 Units	box 126 piece
Package Level 2 Width	245 mm
Package Level 2 Depth / Length	75 mm
Package Level 2 Height	153 mm
Package Level 2 Gross Weight	2.52 kg
Package Level 3 Units	4536 piece

Classifications

Object Classification Code	K
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

