

IEC Contactors

C-2000

Nonreversing and Reversing

AC/DC Controlled, 3-Pole

HP Ratings AC-3 Duty

Three Pole Contactors with Electronic Module - Nonreversing

Max. oper.current		Power AC3					Electrical endurance	Control circuit voltage: AC (50/60Hz)/DC				List Price GO-10C2
Noninductive loads	Motors <440V,3 ~ 50/60Hz	220V 230V	380V 400V	415V 440V	440V	500V	Cat. AC3 Operations	24-60 V Product Number	48-130 V Product Number	100-250 V Product Number	250-500 V Product Number	
AC1 A	AC3 A	kW HP	kW HP	kW HP	kW HP	kW HP						
250	150	45	75	80	80	100	1.7x10 ⁶	CK75CE311W24-60	CK75CE311W48-130	CK75CE311W100-250	CK75CE311W250-500	
250	185	55	90	100	100	110	1.2x10 ⁶	CK08CE311W24-60	CK08CE311W48-130	CK08CE311W100-250	CK08CE311W250-500	
315	205	65	110	125	125	132	1.7x10 ⁶	CK85BE311W24-60	CK85BE311W48-130	CK85BE311W100-250	CK85BE311W250-500	
315	250	75	132	132	132	160	1.5x10 ⁶	CK09BE311W24-60	CK09BE311W48-130	CK09BE311W100-250	CK09BE311W250-500	
450	309	90	160	160	185	200	1.1x10 ⁶	CK95BE311W24-60	CK95BE311W48-130	CK95BE311W100-250	CK95BE311W250-500	
600	420	125	220	230	230	300	1x10 ⁶	CK10CE311W24-60	CK10CE311W48-130	CK10CE311W100-250	CK10CE311W250-500	
700	550	160	280	315	315	400	0.8x10 ⁶	CK11CE311W24-60	CK11CE311W48-130	CK11CE311W100-250	CK11CE311W250-500	
1000	700	220	375	400	425	480	0.7x10 ⁶	CK12BE311W24-60	CK12BE311W48-130	CK12BE311W100-250	CK12BE311W250-500	

100-500 Hp (460V) Reversing¹ Bus Bar Terminals without Lugs

Maximum Current @ 460 V (A) AC-3	3-Phase HP					Auxiliary Contacts ²	24-60 V Product Number	48-130 V Product Number	100-250 V Product Number	250-500 V Product Number	List Price GO-10C2
	@60 Hz, 200V	@60 Hz, 230V	@60 Hz, 460V	@60 Hz, 575V	kW @ 50 Hz, 380/415V						
140A	40	50	100	125	75	1NO-1NC	KAR75CD	KAR75CF	KAR75CJ	KAR75CY	
156A	50	60	125	125	90	1NO-1NC	KAR08CD	KAR08CF	KAR08CJ	KAR08CY	
192A	60	75	150	150	132	1NO-1NC	KAR09BD	KAR09BF	KAR09BJ	KAR09BY	
302A	100	100	250	300	160	1NO-1NC	KAR95BD	KAR95BF	KAR95BJ	KAR95BY	
398A	125	150	300	400	220	1NO-1NC	KAR10CD	KAR10CF	KAR10CJ	KAR10CY	
398A	125	150	300	400	220	1NO-1NC	KAR10BD	KAR10BF	KAR10BJ	KAR10BY	
480A	150	200	400	500	280	1NO-1NC	KAR11CD	KAR11CF	KAR11CJ	KAR11CY	
480A	150	200	400	500	280	1NO-1NC	KAR11BD	KAR11BF	KAR11BJ	KAR11BY	
602A	200	250	500	600	375	1NO-1NC	KAR12BD	KAR12BF	KAR12BJ	KAR12BY	

¹Reversing contactor consists of two (2) contactors, a mechanical interlock, baseplate, power bus bars, cross electrical wiring, and 1NO/1NC side-mounted auxiliary contact for cross electrical and holding interlock. Completely assembled. Note: KAR09 and KAR95 baseplate not suitable for starter assembly.

²NO-1NC side auxiliary contact shipped unassembled (A600, Q600).

