



PRODUCT-DETAILS

CP3-11R-10

CP3-11R-10 Pushbutton



360°

genel Bilgi

Geniřletilmiř Ürün Türü	CP3-11R-10
Ürün Kimlięi	1SFA619102R1111
EAN	7320500552780
Katalog Açıklaması	CP3-11R-10 Pushbutton
Uzun Açıklama	The CP3-11R-10 Pushbutton is: Compact - Pushbutton - Momentary - Extended - Red - Illuminated - Black Plastic - 1NO - Red - 1 NO - 0 NC - , 24 V This Pushbutton is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance.

Ordering

Minimum Sipariř Miktarı	10 piece
Gümrük Tarifesi numarası	8536508090

Popular Downloads

Veri Sayfası, Teknik Bilgi	1SFC151007C02
Talimatlar ve Kılavuzlar	1SFC151011M0201

Dimensions

Ürün Net Genişliği	0.03 m
Ürün Net Yüksekliği	0.03 m
Ürün Net Derinlik / Uzunluk	0.06 m
Ürün Net Ağırlığı	0.025 kg

Technical

Ortam Hava Sıcaklığı	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Extended
Bezel Material	Black Plastic
Illumination	Illuminated
Lamp Type	LED 24V AC/DC
Function	Momentary
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Muhafaza Türü NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Nominal Frekans (f)	50 / 60 Hz Supply Circuit 50 / 60 Hz
Nominal Çalışma Gerilimi	24 V AC/DC Maximum 300 V Supply Circuit 24 V AC/DC
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 2 A (220 / 240 V) 2 A
Power Loss	Maximum 2.5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Connection Type	Screw Clamp
Terminal Türü	Screw Terminals
Sıkma Torku	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental

Koruma Derecesi

Front IP66
Front IP67
Front IP69K
Terminals IP20

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Bilgileri	2CMT2022-006498
RoHS Durumu	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006523
AEEE B2C / B2B	Business To Business
AEEE Kategorisi	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CQC_CN_CN50749
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Uygunluk Beyanı - CE	2CMT2015-005451
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	RU C-CN.ME77.B.00587/20

Container Information

Paket Seviye 1 Birimler	bag 10 piece
Paket Düzey 1 Genişlik	0.125 m
Paket Seviye 1 Derinlik / Uzunluk	0.235 m
Paket Seviye 1 Yükseklik	0.05 m
Paket Seviye 1 Brüt Ağırlık	0.254 kg
Paket Düzey 1 EAN	7320500376386

External Classifications and Standards

Nesne Sınıflandırma Kodu	S
ETIM 6	EC001028 - Push button, complete
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
eSınıf	V11.0 : 27371228
UNSPSC	39122216
IDEA Granüler Kategori Kodu (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2312130
E-Number (Norway)	4372618
E-Number (Sweden)	3717249

katagori

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CP Compact Pushbuttons

