



PRODUCT-DETAILS

CP4-11R-01

CP4-11R-01 Pushbutton



360°

Generell informasjon

Utvidet produkttype	CP4-11R-01
Produkt-ID	1SFA619103R1141
EAN	7320500553619
Katalogbeskrivelse	CP4-11R-01 Pushbutton
Lang beskrivelse	The CP4-11R-01 Pushbutton is: Compact - Pushbutton - Maintained - Extended - Red - Illuminated - Black Plastic - 1NC - Red - 0 NO - 1 NC - , 24 V This Pushbutton is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance.

Ordering

Minimum ordreantall	10 piece
Tolltariffnummer	8536508090

Popular Downloads

Dataark, teknisk informasjon	1SFC151007C02__
Instruksjoner og	1SFC151011M0201

bruksanvisninger

Dimensions

Produktets nettobredde	0.03 m
Produktets netto høyde	0.03 m
Produktets netto dybde/lengde	0.055 m
Produktets nettovekt	0.025 kg

Technical

Omgivelseslufttemperatur	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Extended
Bezel Material	Black Plastic
Illumination	Illuminated
Lamp Type	LED 24V AC/DC
Function	Maintained
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	0
NEMA-kapslingstype	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Nominell frekvens (f)	50 / 60 Hz Supply Circuit 50 / 60 Hz
Nominell driftsspenning	24 V AC/DC Maximum 300 V Supply Circuit 24 V AC/DC
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 2 A (220 / 240 V) 2 A
Power Loss	Maximum 2.5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm² Flexible with Ferrule 2 x 0.5...1.5 mm² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm² Flexible 1 x 0.5 ...1.5 mm² Flexible 2 x 0.5 ...1.5 mm² Solid 1 x 0.5...1.5 mm² Solid 2 x 0.5...1.5 mm²
Connection Type	Screw Clamp
Terminaltype	Screw Terminals
Tiltrekningsmoment	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity UL/CSA	1x 22...14 AWG 2x 22...14 AWG
----------------------------	----------------------------------

Environmental

Beskyttelsesgrad	Front IP66 Front IP67 Front IP69K Terminals IP20
------------------	---

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS-informasjon	2CMT2022-006498
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C/B2B	Business To Business
WEEE-kategori	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CQC_CN_CN50749
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Samsvarserklæring - CE	2CMT2015-005451
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	RU C-CN.ME77.B.00587/20

Container Information

Pakkenivå 1 enheter	bag 10 piece
Pakkenivå 1 bredde	0.125 m
Pakkenivå 1 dybde/lengde	0.235 m
Pakkenivå 1 høyde	0.05 m
Pakkenivå 1 bruttovekt	0.254 kg
Pakkenivå 1 EAN	7320500381502

External Classifications and Standards

Objektklassifiseringskode	S
ETIM 6	EC001028 - Push button, complete
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
e-klasse	V11.0 : 27371228
UNSPSC	39122216
IDEA-granulærkategorikode (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2312165
E-Number (Sweden)	3717260

Kategorier

Lavspenningsprodukter → Startapparater → Betjeningsmateriell → Compact Range → CP Compact Pushbuttons

