

Standard handles & shafts ①

Disconnect
switches
Accessories

Direct mount handle for non-fusible disconnects

Description	For use on	Color	Padlockable	Shaft through handle	Weight	catalog number
Mounts directly on switch. No shaft necessary	OT16-40F_	Black	Yes	Yes	0.05	OHBS12 ②
	OT63-80F_	Black	No	No	0.05	CXBY68989
	OT30/60/100F_		Yes	Yes		OHBS2 ②
Up to 3 padlocks in OFF-position, includes shaft and mechanism	OT200	Black	Yes	Yes	0.22	CXBY68998
	OT400	Black	Yes	Yes	0.44	CXBY68419/6/2M
	OT600	Black	Yes	Yes	0.66	OTV250EK
	OT800	Black	Yes	Yes	0.30	OTV400EK
	OT1200	Black	Yes	Yes	0.30	OTV800EK
Mounts on 12 mm shaft	OETL-NF1600-2000_SW	Metal	No	Yes	0.80	OTV1000EK
						YASDA-34

Direct mount handle for fusible disconnects

For use on	Description	Marking	Color	Padlockable	Weight (lbs)	Catalog number
OS30	No shaft required	O/I/Test	Black	Yes	0.10	OHBS5
OS60 - OS200	No shaft required	O/I/Test	Black	Yes	0.30	OSV200BK
OS400	No shaft required	O/I/Test	Black	Yes	0.75	OSV400BK
OS600-OS800	No shaft required	O/I/Test	Black	Yes	2.43	OSV800DK
OS1200	No shaft required	O/I/Test	Black	Yes	3.30	OSV1250DK

Selector handles for door mounted switches

UL/NEMA Type	IEC Type	Color	Defeatable	Padlockable	Weight (lbs)	Catalog number
Snap-on mounting - for use on OT16FT3 - OT40FT3						
1	IP54	Black	No	No	0.10	OHBS1PH
1	IP54	Black	No	Yes	0.13	OHBS3PH
1, 3R, 12	IP65	Black	No	Yes	0.17	OHBS2PJ
Screw mounting - for use on OT16-100FT3. For OT30FT3, OT60FT3 and OT100FT3 use OH_2_ only						
1	IP54	Black	No	No	0.11	OHBS1RH
1	IP54	Black	No	Yes	0.14	OHBS3RH
1, 3R, 12	IP65	Black	No	Yes	0.18	OHBS2RJ

3 Position selector handles for double throw switches - for use with .24 x .24" (6mm) OXS6X shafts

UL/NEMA Type	IEC Type	Markings	Color	Defeatable	Padlockable	Weight (Lbs.)	Catalog number
1, 3R, 12	IP65	I/O/II, ON/OFF/ON	Black	Yes	Yes	0.16	OHBS2AJE011

3 Position pistol handles for double throw switches

UL/NEMA Type	IEC Type	Markings	Color	Defeatable	Padlockable	Weight (Lbs.)	Catalog number 6 mm	Catalog number 12 mm
1, 3R, 12	IP65	I/O/II, ON/OFF/ON	Black	Yes	Yes	0.29/0.33	OHB65J6E011	OHB145J12E011
1, 3R, 12, 4, 4X	IP66		Black	Yes	Yes	0.29/ 0.33	OHB65L6E011	OHB145L12E011
1, 3R, 12	IP65		Black	Yes	Yes	0.30/0.37	OHB80J6E011	OHB175J12E011
1, 3R, 12, 4, 4X	IP66		Black	Yes	Yes	0.30/0.37	OHB80L6E011	OHB175L12E011
1, 3R, 12	IP65		Black	Yes	Yes	0.88	OHB200J12PE011	OHB200J12PE011
1, 3R, 12	IP65		Black	Yes	Yes	1.19	OHB274J12E011	OHB274J12E011
1, 3R, 12, 4, 4X	IP66		Black	Yes	Yes	1.19	OHB274L12E011	OHB274L12E011

CXBY68989

Direct mount handle for double throw switches

For use on	Description	Marking	Color	Padlockable	Weight (lbs)	Catalog number
OT16...80F_C	No shaft required	— ③	Black	No	0.03	OHBS3
OT30, 60, 100F_C	No shaft required		Black	No	0.02	OHBS9
OT16...80F_C	No shaft required		Black	Yes	0.05	OHBS2
OT30, 60, 100F_C	No shaft required		Black	Yes	0.04	OHBS11
OT200U_C	No shaft required	O/I/Test	Black	Yes	0.10	OTV250ECK
OT400U_C	No shaft required	O/I/Test	Black	Yes	0.30	OTV400ECK
OT600U_C	No shaft required	O/I/Test	Black	Yes	0.75	OTV800ECK
OT800U_C	No shaft required	O/I/Test	Black	Yes	2.43	OTV1000ECK

CXBY68419/6/2M

- ① Red/Yellow handles are available by substituting the OHB prefix with OHY.
All handles are plastic unless otherwise noted as metal or stainless steel.
② Suitable for 3 & 4 pole versions only. Not for use with 6 or 8 pole.
③ Markings are on the disconnect, not on the handles.