

Power Circuit Breakers T&B Catalog Number:

UPC Number:	
Status:	
Description:	

D3HFKFB00B000XC 66201999870 Active

3 pole, 3200 amps rated at 600V AC, Fixed, IEC rated, Emax power circuit breaker, with an electronic PR121/P trip unit, LSI operation and 100kA at 415V interrupt current rating

|--|

	Compact design
	Improved safety due to double insulation of live
	parts and total segregation between phases
	Same height and depth for both withdrawable and
	fixed versions
Application	
	Circuit breaker for general protection such as
	plants, user complexes and electric lines
	Can be used to protect equipment feeder lines for
	electrical machines such as generators, motors,
	transformers or capacitors
	The UL 1066 certification allows Emax to be used
	in UL 1558 switchgear, UL891 low voltage switch-
	boards and CSA C22.2 no. 31 switchgear assem-
	blies
General	
Тгір Туре	PR121/P
Trip Unit Function	LSI
Breaking Capacity	High
Closing Operation	Manual
Fixed/Drawout	Fixed
Frame Size	E3
Locking Provisions	Padlock provision (open)
Number of Poles	3
Series	D3
Contacts	10 Aux
Auxiliary Contacts	10
Approvals	
UL Class	UL 1066
Dimension Information	
H x W x D (inches)	16.6 x 15.91 x 11.9
Specifications	
Rated Current (Amps)	3200
Rated Voltage AC	600
Rating Plug	3200
Interrupt Rating	100kA at 415V AC
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	158.73 lbs. Each



Certifications



File Nbr: UL 1066

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com