

Power Circuit Breakers T&B Catalog Number:

UPC Number:
Status:
Description:

D3SCFFB00B000XC 66201947640 Active

3 pole, 1600 amps rated at 600V, IEC rated, with an interupt rating of 75kA At 660/690V, and standard breaking capacity, Emax E2 air circuit breaker

Features

	Compact design
	Improved safety due to double insulation of live parts and total segregation between phases
	Same height and depth for both withdrawable and fixed versions
Application	
	Circuit breaker for general protection such as
	plants, user complexes and electric lines
	Can be used to protect equipment feeder lines for
	electrical machines such as generators, motors,
	transformers or capacitors
General	
Тгір Туре	PR121/P
Trip Unit Function	LSI
Breaking Capacity	Standard
Closing Operation	Manual
Fixed/Drawout	Fixed
Frame Size	E3
Locking Provisions	Padlock provision (open)
Number of Poles	3
Series	D3
Contacts	10 Aux
Auxiliary Contacts	10
Specifications	
Rated Current (Amps)	1600
Rating Plug	1600
Interrupt Rating	75kA At 660/690V
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	148 lbs. Each
-	

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com