

Power Circuit Breakers T&B Catalog Number:

D3SDGFB00B000XC

UPC Number: 66201946090

Status: Active

Description:

3 pole, 2000 amps rated at 600V, IEC rated, with an interupt rating of 75kA At 660/690V, and standard breaking capacity, Emax E2 air circuit breaker

breaker	
Features	
	Compact design
	Improved safety due to double insulation of live parts and total segregation between phases Same height and depth for both withdrawable and fixed versions
Application	
	Circuit breaker for general protection such as plants, user complexes and electric lines
	Can be used to protect equipment feeder lines for electrical machines such as generators, motors, transformers or capacitors
General	
Trip Type	PR121/P
Trip Unit Function	LSI
Breaking Capacity	Standard
Closing Operation	Manual
Fixed/Drawout	Fixed
Frame Size	E3
Locking Provisions	Padlock provision (open)
Number of Poles	3
Series	D3
Contacts	10 Aux
Auxiliary Contacts	10
Specifications	
Rated Current (Amps)	2000
Rating Plug	2000
Interrupt Rating	75kA At 660/690V
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	158.73 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com