



D4NS-1CF

Safety-door switch, Plastic, Tongue operated, PG13.5 (1-conduit), 2NC/1NO (slow-action)

Specifications

Door switch type	Key-operated
Guard-lock	×
Material housing	Resin
Material head	Resin
Ambient temperature (operating)	-30-70 °C
Direction of operation	Adjustable
Door contacts NC	2
Door contacts NO	1
Switch action	Slow action
Make before break	×
LED indicator	×
Connection method	Terminal block
Cable length	0 m
Degree of protection (IP)	IP67
Conduit size	PG13.5
Number of conduits	1
Shape	Cuboid
Overall length	96 mm
Height of sensor	30 mm
Width of sensor	31 mm

Accessories



D4DS-K1

Operation key for D4NL/NS; horizontal mounting



D4DS-K2

Operation key for D4NL/NS; vertical mounting



D4DS-K3

Operation key for D4NL/NS; adjustable mounting (horizontal)



D4DS-K5

Operation key for D4NL/NS; adjustable mounting (horizontal/vertical)

Downloads

CAD Library



**D4NS Safety-door
Switch
Datasheet**

EN PDF 642 KB



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**Machine Safety
Catalogue**

EN PDF 9.91 MB



**Machine Safety Solution
Brochure**

EN PDF 2.86 MB



**Safety Component
Selection Guide
Brochure**

EN PDF 10.8 MB



**Safety Interlock
Switches
Brochure**

EN PDF 1.52 MB



**Safety Solution
Advanced Guide
Guide**

EN PDF 2.57 MB



**Safety Solution Basic
Guide
Guide**

EN PDF 14.4 MB

