

PRODUCT-DETAILS

DB25/25A-RT Single Mounting Kit



General Information	
Extended Product Type	DB25/25A-RT
Product ID	1SAZ201108R0011
Catalog Description	DB25/25A-RT Single Mounting Kit
Long Description	DB25/25A-RT Single Mounting Kit
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Dimensions	
Product Net Width	44 mm
Product Net Height	70.5 mm
Product Net Depth / Length	85.8 mm
Product Net Weight	0.055 kg

DB25/25A-RT 2/3

Technical	
Rated Operational Voltage	Main Circuit 690 V AC
Rated Frequency (f)	Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 6 kV
Rated Insulation Voltage (U _i)	690 V
Number of Poles	3F
Pollution Degree	3
Environmental	
Ambient Air Temperature	Operation -25 +55 °C
	Storage -40 +70 °C
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006528
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope
Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	238 mm
Package Level 1 Height	140 mm
Package Level 1 Depth / Length	82 mm
Package Level 1 Gross Weight	0.655 kg
Classifications	
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392

DB25/25A-RT 3/3

Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Control Products} \rightarrow \text{Contactors} \rightarrow \text{Thermal Overload Relays}$

