DB25/32A 1/3



PRODUCT-DETAILS

## DB25/32A Single Mounting Kit



General Information	DD0F100A
Extended Product Type	DB25/32A
Product ID	1SAZ201108R0002
EAN	4013614237744
Catalog Description	DB25/32A Single Mounting Kit
Long Description	DB25/32A Single monting kit for TA25DU
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Popular Downloads	
Instructions and Manuals	2CDC106090M6801
Dimension Diagram	1SAZ200403F0001

DB25/32A 2/3

Product Net Width 44 r Product Net Height 84.5 r Product Net Depth / 85.8 r Length 97 coluct Net Weight 0.08  Technical 88 column 1
Product Net Depth / S5.8 r Length  Product Net Weight 0.08  Technical  Rated Operational Voltage Main Circuit 690 V Rated Operational Current AC-3 (I <sub>e</sub> )  Rated Frequency (f) Main Circuit 50 Main Circuit 60 Voltage (U <sub>imp</sub> )  Rated Insulation Voltage 69 (U <sub>i</sub> )  Number of Poles  Pollution Degree
Length Product Net Weight  Technical  Rated Operational Voltage Main Circuit 690 V Rated Operational Current 3. AC-3 (I <sub>e</sub> )  Rated Frequency (f) Main Circuit 50 Main Circuit 60 Main Circuit 60 V Rated Impulse Withstand Voltage (U <sub>imp</sub> )  Rated Insulation Voltage (0, 0) Rated Insulation Voltage (0, 0)  Rated Insulation Voltage (0, 0)  Number of Poles  Pollution Degree
Product Net Weight  Technical  Rated Operational Voltage Rated Operational Current AC-3 (I <sub>e</sub> )  Rated Frequency (f)  Rated Impulse Withstand Voltage (U <sub>imp</sub> )  Rated Insulation Voltage (U <sub>i</sub> )  Number of Poles  Pollution Degree
Technical  Rated Operational Voltage Main Circuit 690 V Rated Operational Current 3 AC-3 (I <sub>e</sub> )  Rated Frequency (f) Main Circuit 50 Main Circuit 60 Rated Impulse Withstand Voltage (U <sub>imp</sub> )  Rated Insulation Voltage (U <sub>ipp</sub> )  Number of Poles Pollution Degree
Rated Operational Voltage Rated Operational Current AC-3 (I <sub>e</sub> ) Rated Frequency (f) Rated Frequency (f) Rated Impulse Withstand All Circuit 50 Main Circuit 60 All Circuit 60 Main Circuit 60 All Circuit 60 Main Circuit 60 Main Circuit 60 Main Circuit 60 All Circuit 60 Main Circuit 60 All Circuit 50 All Circuit 60 All Circuit 50 All Circuit 60 All Cir
Rated Operational Voltage Rated Operational Current AC-3 (I <sub>e</sub> ) Rated Frequency (f) Rated Impulse Withstand Voltage (U <sub>imp</sub> ) Rated Insulation Voltage (U <sub>i</sub> ) Number of Poles Pollution Degree
Rated Operational Current AC-3 (I <sub>e</sub> )  Rated Frequency (f)  Rated Impulse Withstand Voltage (U <sub>imp</sub> )  Rated Insulation Voltage (U <sub>i</sub> )  Number of Poles  Pollution Degree
Main Circuit 60 Rated Impulse Withstand Voltage (U <sub>imp</sub> ) Rated Insulation Voltage (U <sub>i</sub> )  Number of Poles Pollution Degree
Voltage (Ū <sub>imp</sub> )  Rated Insulation Voltage 69 (U <sub>i</sub> )  Number of Poles  Pollution Degree
Rated Insulation Voltage (U <sub>i</sub> )  Number of Poles  Pollution Degree
Pollution Degree
Suitable For TA25
Standards UL 6094 
Voltage UL/CSA
Environmental
Ambient Air Temperature Operation -25 +55 Storage -40 +70
Material Compliance  Conflict Minerals Reporting Template (CMRT)  9AKK108467A56
Conflict Minerals 9AKK108467A56 Reporting Template (CMRT)
Conflict Minerals         9AKK108467A56           Reporting Template         (CMRT)           REACH Declaration         2CMT2021-0062
Conflict Minerals         9AKK108467A56           Reporting Template         CMRT)           CEMRT)         2CMT2021-0062           REACH Declaration         2CMT2021-0062           ROHS Information         2CMT2021-0062
Conflict Minerals         9AKK108467A56           Reporting Template         (CMRT)           REACH Declaration         2CMT2021-0062           RoHS Information         2CMT2021-0062           RoHS Status         Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 20           Toxic Substances Control         2CMT2023-0068
Conflict Minerals         9AKK108467A56           Reporting Template         (CMRT)           REACH Declaration         2CMT2021-0062           RoHS Information         2CMT2021-0062           RoHS Status         Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 20

2024/12/03

Subject to change without notice

© 2024 ABB. All rights reserved.

DB25/32A 3/3

RINA Certificate No Certificate Needed
UL Certificate E48139-19970507

Container Information	
Package Level 1 Units	10 piece
Package Level 1 Width	238 mm
Package Level 1 Height	140 mm
Package Level 1 Depth / Length	82 mm
Package Level 1 Gross Weight	0.905 kg
Package Level 1 EAN	4013614515125

Classifications	
Object Classification Code	Q
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	31162313
IDEA Granular Category Code (IGCC)	2988 >> Mounting kits
E-Number (Norway)	4116894

## Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Contactors\ \rightarrow\ Thermal\ Overload\ Relays$ 

