



Main

Range	Linergy
Product name	TR
Product or component type	Terminal block
Technology type	Screw technology
Terminal block type	Passthrough, with Telequick universal foot
Terminal block level	1
Mounting mode	Clip-on mounting on Telequick mounting plate Clip-on mounting on 35 mm symmetrical DIN rail Clip-on mounting on 35 mm notched symmetrical rail Clip-on mounting on 35 mm asymmetrical rail
Nominal cross section	4 mm ²
Length	48 mm
Colour	Grey
Number of poles	2
Quantity per set	Set of 10

Complementary

Width	14 mm
Height	56.5 mm on 35 mm notched symmetrical rail 54 mm on 35 mm asymmetrical rail 49 mm on 35 mm symmetrical DIN rail 42 mm on Telequick mounting plate
Cable cross section	0.75...2.5 mm ² , flexible with cable end 1...6 mm ² , solid 1...4 mm ² , flexible without cable end
[Ue] rated operational voltage	750 V AC/DC conforming to VDE group C 750 V AC/DC conforming to UTE category C 600 V, 20...12 AWG CSA
[Ie] rated operational current	30 A, 20...12 AWG CSA 30 A conforming to VDE group C 30 A conforming to UTE category C
Product weight	26 g
Range compatibility	TeSys Prisma - P Prisma - G

Environment

Product certifications	CSA
------------------------	-----