

Peripheral Devices for Environment-resistive Slaves





Peripheral Devices for DeviceNet Communications

Ordering Information






● Environment-resistive Connection Products (for Thin Cable, M12 Micro Connectors)

Product	Appearance	Model	Specifications
Sealed Assembling-type Connector (male)		XS2G-D5S7	For communications (plug)
Sealed Assembling-type Connector (female)		XS2C-D5S7	For communications (socket)
Sealed T-branch Connector		DCN2-1	For 1 branch line
Sealed Connector with Terminating Resistor		DRS2-1	Plug
		DRS2-2	Socket
Cables with Sealed Connectors		DCA1-5CNC5W1	Length (L): 0.5 m
		DCA1-5CN01W1	Length (L): 1 m
		DCA1-5CN02W1	Length (L): 2 m
		DCA1-5CN03W1	Length (L): 3 m
		DCA1-5CN05W1	Length (L): 5 m
		DCA1-5CN10W1	Length (L): 10 m
		DCA1-5CNC5F1	Length (L): 0.5 m
		DCA1-5CN01F1	Length (L): 1 m
		DCA1-5CN02F1	Length (L): 2 m
		DCA1-5CN03F1	Length (L): 3 m
		DCA1-5CN05F1	Length (L): 5 m
		DCA1-5CN10F1	Length (L): 10 m
		DCA1-5CNC5H1	Length (L): 0.5 m
		DCA1-5CN01H1	Length (L): 1 m
		DCA1-5CN02H1	Length (L): 2 m
		DCA1-5CN03H1	Length (L): 3 m
		DCA1-5CN05H1	Length (L): 5 m
		DCA1-5CN10H1	Length (L): 10 m
Shielded Panel-mounting Connectors (female)		DCA1-5CNC5P1	Panel-mounting connector (socket) with 0.5-m cable
		XS2P-D522-2	Panel-mounting connector socket
Shielded Panel-mounting Connectors (male)		DCA1-5CNC5M1	Panel-mounting connector (plug) with 0.5-m cable
		XS2M-D524-4	Panel-mounting connector (plug) with solder-cup terminals
Waterproof cover (for socket)		XS2Z-22	Used to cover an unused connector section
Dust cover (for socket)		XS2Z-15	

● Environment-resistive Models (for Thin Wires and M12 Micro Connectors)

Product	Appearance		Model	Specifications	
Sealed T-branch Connector			DCN2-1S	For 1 branch line	
Sealed Assembling type Connector (female)			DRS2-1S	Plug	
			DRS2-2S	Socket	
Connectors with Shielded Cables			DCA1-5CSC5W1	Length (L): 0.5 m	Cable with connectors on both ends
			DCA1-5CS01W1	Length (L): 1 m	
			DCA1-5CS02W1	Length (L): 2 m	
			DCA1-5CS03W1	Length (L): 3 m	
			DCA1-5CS05W1	Length (L): 5 m	
			DCA1-5CS10W1	Length (L): 10 m	
			DCA1-5CSC5F1	Length (L): 0.5 m	Cable with connector on one end (socket)
			DCA1-5CS01F1	Length (L): 1 m	
			DCA1-5CS02F1	Length (L): 2 m	
			DCA1-5CS03F1	Length (L): 3 m	
			DCA1-5CS05F1	Length (L): 5 m	
			DCA1-5CS10F1	Length (L): 10 m	
			DCA1-5CSC5H1	Length (L): 0.5 m	Cable with connector on one end (plug)
			DCA1-5CS01H1	Length (L): 1 m	
			DCA1-5CS02H1	Length (L): 2 m	
			DCA1-5CS03H1	Length (L): 3 m	
			DCA1-5CS05H1	Length (L): 5 m	
			DCA1-5CS10H1	Length (L): 10 m	
Shielded Branch Relay Box			DCN2-S4C5H1	4 ports, 0.5-m cable	
			DCN2-S8C5H1	8 ports, 0.5-m cable	

● Environment-resistive Models for Thick Wires with 7/8-16UN Mini Connectors

Product	Appearance		Model	Specifications	
Sealed T-branch Connector			DCN3-11	T-branch Connector	
			DCN3-12	T-branch Connector (Branch connector is M12.)	
Sealed Connector with Terminating Resistor			DRS3-1	Plug	
Cables with Sealed Connectors			DCA2-5CN01W1	Length (L): 1 m	Cable with connectors on both ends
			DCA2-5CN02W1	Length (L): 2 m	
			DCA2-5CN05W1	Length (L): 5 m	
			DCA2-5CN10W1	Length (L): 10 m	
			DCA2-5CN01F1	Length (L): 1 m	Cable with connector on one end (socket)
			DCA2-5CN02F1	Length (L): 2 m	
			DCA2-5CN05F1	Length (L): 5 m	
			DCA2-5CN10F1	Length (L): 10 m	
			DCA2-5CN01H1	Length (L): 1 m	Cable with connector on one end (plug)
			DCA2-5CN02H1	Length (L): 2 m	
			DCA2-5CN05H1	Length (L): 5 m	
			DCA2-5CN10H1	Length (L): 10 m	
			DCA1-5CN01W5	Length (L): 1 m	Cable with connectors on both ends Thin cable M12 socket
			DCA1-5CN02W5	Length (L): 2 m	
			DCA1-5CN05W5	Length (L): 5 m	
			DCA1-5CN10W5	Length (L): 10 m	
Panel-mounting Connector (female)			DCA2-5CNC5P1	Panel-mounting connector (socket) with 0.5-m cable	
Panel-mounting Connector (male)			DCA2-5CNC5M1	Panel-mounting connector (plug) with 0.5-m cable	
Panel-mounting Connector (male)			XS4M-D521-1	Panel-mounting connector (plug) DIP terminals	
Waterproof Cap (for Plug)	-		XS4Z-11	Used to cover an unused connector section.	
Waterproof Cap (for Socket)	-		XS4Z-12		