NFC cartridge fuses, TeSys GS, cylindrical 10mm x 38mm, fuse type aM, 500VAC, 4A, without striker, set of 10 parts

DF2CA04

Main

range of product	TeSys fuse-disconnector
product or component type	Cartridge fuse
Device short name	DF2
[Ue] rated operational voltage	500 V AC
Fuse size	10 x 38 mm
Fuse type	NFC
Quantity per set	Set of 10

Complementary

[In] rated current	4 A 500 V
Fuse curve	AM
net weight	0.01 kg

Packing Units

16 Oct 2024

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.3 cm
Package 1 Width	10.8 cm
Package 1 Length	4 cm
Package 1 Weight	7 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1.3 cm
Package 2 Width	10.8 cm
Package 2 Length	4 cm
Package 2 Weight	78 g
Unit Type of Package 3	S01
Number of Units in Package 3	720
Package 3 Height	15 cm
Package 3 Width	15 cm
Package 3 Length	40 cm

Package 3 Weight 5.8 kg

Contractual warranty

Warranty 18 months

16 Oct 2024

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Pvc Free	
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins