Specifications

NFC cartridge fuses, TeSys GS, cylindrical 10mm x 38mm, fuse type aM, 400VAC, 25A, without striker, set of 10 parts

DF2CA25

Main

range of product	TeSys fuse-disconnector	
product or component type	Cartridge fuse	
Device short name	DF2	
[Ue] rated operational voltage	400 V AC	
Fuse size	10 x 38 mm	
Fuse type	NFC	
Quantity per set	Set of 10	

Complementary

[In] rated current	25 A 400 V
Fuse curve	AM
net weight	0.01 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.4 cm
Package 1 Width	5.4 cm
Package 1 Length	8 cm
Package 1 Weight	7 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1.4 cm
Package 2 Width	5.4 cm
Package 2 Length	8 cm
Package 2 Weight	79 g
Unit Type of Package 3	S01
Number of Units in Package 3	720
Package 3 Height	15 cm
Package 3 Width	15 cm
Package 3 Length	40 cm

Package 3 Weight

6.04 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	
Rea	ch Regulation	REACh Declaration
Eu l	Rohs Directive	Compliant EU RoHS Declaration
Chii	na Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Wee	96	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins