




PRODUCT-DETAILS

DP20C2P-F

DP20C2P-F Contactor



360°

General Information	
Extended Product Type	DP20C2P-F
Product ID	1SBX101200R1100
EAN	0888614076266
Catalog Description	DP20C2P-F Contactor
Long Description	DP20C2P-F DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions	
Product Net Depth / Length	60.1 mm

Technical	
Number of Main Contacts NO	2
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Product Name	Definite Purpose Contactors

Technical UL/CSA	
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (220 ... 240 V AC) Single Phase 3 Hp
Full Load Amps Motor Use	20 A
Full Load Amps AC Resistance (Heating)	(600 V AC) 30 A

Environmental	
Ambient Air Temperature	Operation -40 ... +65 °C

Material Compliance	
WEEE B2C / B2B	Business To Business


Certificates and Declarations	
cUL Certificate	cUL_E224401
Declaration of Conformity - CE	EN60947-4-1:2001

Container Information	
Package Level 1 Units	1 piece

Classifications	
Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
IDEA Granular Category Code (IGCC)	4757 >> Definite Purpose Contactors

Categories

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors



360°