



PRODUCT-DETAILS

DP40C3P-4

DP40C3P-4 Contactor



General Information	
Extended Product Type	DP40C3P-4
Product ID	1SBX104300R1500
EAN	0662019755663
Catalog Description	DP40C3P-4 Contactor
Long Description	DP40C3P-4 DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions	
Product Net Depth / Length	73.8 mm

Technical	
Number of Main Contacts NO	3
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Rated Control Supply Voltage (U _s)	480 V

Environmental	
Ambient Air Temperature	Operation -40 ... +65 °C

Technical UL/CSA	
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 3 Hp (208 V AC) Three Phase 10 Hp (220 ... 240 V AC) Single Phase 7.5 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp (550 ... 600 V AC) Three Phase 25 Hp
Full Load Amps AC Resistance (Heating)	(600 V AC) 50 A
Full Load Amps Motor Use	40 A
Locked Rotor Amps	(480 V AC) 200 A (600 V AC) 160 A

Certificates and Declarations	
cUL Certificate	cUL_E224401
Declaration of Conformity - CE	EN60947-4-1:2001

Container Information	
Package Level 1 Units	1 piece

Classifications	
Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching

Categories

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

