



## Alternate Catalog No. DP75C3P-1 Catalog No. 1SBX107300R1200

Description: DP CONTR, 75A,3P,120VAC

UPC No 804325552080

 $\label{loss:contactor} \textbf{Home} > \textbf{Contactors} \ \& \ \textbf{Starters} > \textbf{Definite Purpose Contactor}$ 

DP75C3P-1 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Descriptors	
Category	Definite Purpose Contactor
Specifications	
Product Type	DP Contactor
Amps Frame	75 A
Poles	3P
Coil Voltage	120 V
Bulk Pack	Single
Special Termination	Standard
Order Multiple	1
Termination	#14-1 AWG lug with dual quick connectors
Dimensions	
Length	5.118 in.
Width	3.46 in.
Height	5.2 in.
Weight	3.3 lb.
Operating Performance	
Operating temperature	-40+65 oC
Insulation Class	130 oC Class B
Ordering	
Customs Tariff Number	85365080

tnb.ca.abb.com/en/ Created on: 11/27/2024

tnb.ca.abb.com/en/ Created on: 11/27/2024