



Accessories

for 16A – 100A Non-fusible disconnect switches

Base & DIN rail mounted



OTS32T3
OTS63T3
OTS125T3


OTS32T1
OTS63T1
OTS125T1




DS-SA1 DS-SA2




STL-ST



OP_2



OP_2EN1



OETL-ZW16



DIN RAIL

Terminal shrouds* — snap on mounting for line or load side

Description	For use on:	Weight (lbs.)	Catalog number	List price
3 pole includes one shroud for line or load side	OT16, OT25, OT32	0.02	OTS32T3	
	OT45, OT63	0.02	OTS63T3	
	OT30, OT60, OT100	0.02	OTS125T3	
4th pole includes one shroud for line or load side	OTP_32EP	0.02	OTS32T1	
	OTP_63EP	0.02	OTS63T1	
	OTP_125EP	0.02	OTS125T1	

* All disconnects are IP20 touch safe as standard. Terminal shrouds provide an additional level of protection.

Padlocking adapter

Description	For use on:	Weight (lbs.)	Catalog number	List price
Adapter for one padlock with a max. 0.137" shackle	OT30, OT45 - OT100	0.02	DS-SA1	
Padlock for DS-SA1		0.22	DS-SA2	
Adapter and padlock		0.24	DS-SA3	

Labelling accessories

Description	For use on:	Package quantity	Catalog number	List price
1 Pkg. of label carriers 1 Pkg of blank description labels	OT30, OT45 – OT100	100 pieces 315 pieces	STL-ST ST-E	

Legend plates for selector handles

Description	For use on:	Catalog number	List price
Blank plate			
Black	OH_1_ & OH_3_	OPB1	
Yellow	OH_1_ & OH_3_	OPY1	
Black	OH_2_	OPB2	
Yellow	OH_2_	OPY2	
Plate marked with: MAIN SWITCH			
Black	OH_1_ & OH_3_	OPB1EN1	
Yellow	OH_1_ & OH_3_	OPY1EN1	
Black	OH_2_	OPB2EN1	
Yellow	OH_2_	OPY2EN1	

Locking accessories

Description	For use on:	Weight (lbs.)	Catalog number	List price
Cam attachment for Kirk Key, Castell, Lowe & Fletcher and Ronis interlock. For adapting to the interlock system. The interlock is not included.	5, 6 & 8mm shafts	0.29	OETL-ZW16	

DIN rail

Description	For use on:	Weight (lbs.)	Length inches/mm	Catalog number	List price
35mm DIN Rail	OT16 – OT100	2.96	39.4/1000	DIN RAIL	

Shaft support

Description	For use on:	Weight (lbs.)	Catalog number	List price
Shaft support	OT16 – OT100	0.30	OETL-ZX58	

The shaft support is used for disconnects installed in deep enclosures.

Non-Fusible