



PRODUCT-DETAILS

DS2417MP000  
200A,PLG,3P4W,MG,417,3P208V



General Information	
Extended Product Type	DS2417MP000
Product ID	7TAA057030R0539
Catalog Description	200A,PLG,3P4W,MG,417,3P208V
Long Description	MaxGard Male Plug, 200 Amp, 3 Pole 4 Wire, 30 208V, 400Hz

Ordering	
UPC	708917089063
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA
Package Level 1 Width	152.4 mm 6 in
Package Level 1 Height	139.7 mm 5.5 in

Package Level 1 Depth / Length	355.6 mm 14 in
--------------------------------	-------------------

Additional Information

Application	Electrical hook-up of mobile medical imaging (MMI trailers).
Brand / Label	Russellstoll
Current Rating	200 A
Effective Date	19960919
Material	Cast Aluminum
Number of Conductors	4
Number of Poles	3P
Product Name	Cylindrical multicontact connectors
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Voltage Rating	208 V

Certificates and Declarations

Data Sheet, Technical Information	DS2417MP000
-----------------------------------	-------------

External Classifications and Standards

ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

