



PRODUCT-DETAILS

DS3404FP00K
30A,FEM-PLG,3P4W,MG,404,00K,3P480V



General Information	
Extended Product Type	DS3404FP00K
Product ID	7TAA057030R0627
Catalog Description	30A,FEM-PLG,3P4W,MG,404,00K,3P480V
Long Description	MaxGard Female Connector with Control Contacts, 30 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

Ordering	
UPC	708917146728
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA
Package Level 1 Width	0.025 mm 0.001 in
Package Level 1 Height	0.025 mm

	0.001 in
Package Level 1 Depth /	0.025 mm
Length	0.001 in

Additional Information

Application	For use in "People Movers" which require aire conditioning and heater unit power when docked at end of line locations for maintenance and overhaul, ex: Dulles Airport.
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	19960411
Material	Cast Aluminum
Number of Conductors	4
Number of Poles	3P
Product Name	Other
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Voltage Rating	480 V

Certificates and Declarations

Data Sheet, Technical Information	DS3404FP00K
-----------------------------------	-------------

External Classifications and Standards

ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

