



Siemens Energy Management Residential Specialty Load Centers: Small Circuit (2-10) . Type: Series EQ, Main Lug Special Features: Temperature Rating: 60/75 DEG C; Bus Bar Type: Copper Application: For Use As Service Entrance Equipment Standard: UL Listed Voltage Rating: 120/240 Amperage Rating: 125 Phase: 1 Wiring Configuration: 3-Wire SN Bus Rating: 125 Interrupt Rating: 100 Circuit Breaker Type: QP, QPH, HQP Number Of Spaces: 2 Number Of Feeders: 4 Size: 7-1/8 IN Width X 4-1/4 IN Depth X 17-1/8 IN Height. CB ENCL 2-4CT 1P3W 125A CU BUS FLSH N-1

General technical data	
configuration of the busbars	125
fastening method	Flush
number of circuits in a trunking unit	4
phase number	1
suitability for operation	For Use As Service Entrance Equipment
Electricity	
ampacity	125 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V
Switching capacity	
switching capacity current according to EN 60898 rated value	100 A
Model	
product brand name	Siemens
product type designation	Series EQ, Main Lug
special product feature	Temperature Rating: 60/75 DEG C; Bus Bar Type: Copper
type of wiring of distribution board	3-Wire SN
Mechanical Design	
depth [in]	17.12 in
height [in]	4.25 in
number of modular width units for installation width	2
size of the circuit-breaker	QP, QPH, HQP
width [in]	7.12 in
General product approval	
certificate of suitability	UL Listed

last modified:

1/6/2021 

