



Omron Automation & Safety



E2A-M12KN08-WP-B2 5M

Penerangan Produk	M12 UNSH,NPB,8MM,PNP,NC,5M CAB
Status RoHS	Lead percuma / RoHS Compliant
Kapal Dari	Hong Kong
Cara Penghantaran	DHL/Fedex/TNT/UPS/EMS

Spesifikasi E2A-M12KN08-WP-B2 5M

NOMBOR BAHAGIAN	E2A-M12KN08-WP-B2 5M
PENGELUAR	Omron Automation & Safety
PENERANGAN	M12 UNSH,NPB,8MM,PNP,NC,5M CAB
STATUS STATUS PERCUMA / ROSH STATUS	Lead percuma / RoHS Compliant
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Cable Leads
PERISAI	Unshielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	0.315" (8mm)
RESPON FREKUENSI	800Hz
PAKEJ / KES	Cylinder, Threaded - M12
JENIS OUTPUT	PNP-NC, 3-Wire
NAMA LAIN	E2A-M12KN08-WP-B2 5M-ND E2A-M12KN08-WP-B25M E2AM12KN08WPB25M
SUHU OPERASI	-40°C ~ 85°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Nickel-Plated Brass
PENGILANG STANDARD LEAD TIME	15 Weeks
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 0.315" (8mm) IP67, IP69K Cylinder, Threaded - M12