

E2A-M12KN08-WP-C2 5M

|                   |                                   |
|-------------------|-----------------------------------|
| Penerangan Produk | M12 UNSH,NPB,8MM,NPN,NC,5M CAB    |
| Status RoHS       | Memimpin percuma / RoHS Compliant |
| Keadaan Stok      | 1156 pcs stock                    |
| Kapal Dari        | Hong Kong                         |
| Cara Penghantaran | DHL/Fedex/TNT/UPS/EMS             |



Spesifikasi E2A-M12KN08-WP-C2 5M

|                                     |                                                                              |
|-------------------------------------|------------------------------------------------------------------------------|
| NOMBOR BAHAGIAN                     | E2A-M12KN08-WP-C2 5M                                                         |
| PENGELUAR                           | Omron Automation & Safety                                                    |
| PENERANGAN                          | M12 UNSH,NPB,8MM,NPN,NC,5M CAB                                               |
| STATUS STATUS PERCUMA / ROSH STATUS | Memimpin percuma / RoHS Compliant                                            |
| KUANTITI TERSEDIA                   | 1156 pcs                                                                     |
| LEMBARAN DATA                       |                                                                              |
| VOLTAN - BEKALAN                    | 10 V ~ 32 V                                                                  |
| STYLE PENAMATAN                     | Cable Leads                                                                  |
| PERISAI                             | Unshielded                                                                   |
| SIRI                                | E2A                                                                          |
| JENIS SENSOR                        | Inductive                                                                    |
| SENSING JARAK                       | 0.315" (8mm)                                                                 |
| RESPON FREKUENSI                    | 800Hz                                                                        |
| PAKEJ / KES                         | Cylinder, Threaded - M12                                                     |
| JENIS OUTPUT                        | NPN-NC, 3-Wire                                                               |
| NAMA LAIN                           | E2A-M12KN08-WP-C2 5M-ND<br>E2A-M12KN08-WP-C25M<br>E2AM12KN08WPC25M           |
| SUHU OPERASI                        | -40°C ~ 85°C                                                                 |
| TAHAP SENSITIVITI LEMBAPAN (MSL)    | 1 (Unlimited)                                                                |
| BAHAN - BADAN                       | Nickel-Plated Brass                                                          |
| STATUS STATUS PERCUMA / ROSH STATUS | Lead free / RoHS Compliant                                                   |
| PERLINDUNGAN INGRESS                | IP67, IP69K                                                                  |
| PETUNJUK                            | LED                                                                          |
| PENERANGAN TERPERINCI               | Inductive Proximity Sensor 0.315" (8mm) IP67, IP69K Cylinder, Threaded - M12 |