



E2A-M12KS04-M1-C3

Product description	PROXIMITY SENS M12 4MM NPN NO+NC
RoHs Status	Lead free / RoHS Compliant
Stock Condition	914 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS

Specifications of E2A-M12KS04-M1-C3

PART NUMBER	E2A-M12KS04-M1-C3
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	PROXIMITY SENS M12 4MM NPN NO+NC
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	914 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Connector
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.157" (4mm)
RESPONSE FREQUENCY	1kHz
PACKAGE / CASE	Cylinder, Threaded - M12
OUTPUT TYPE	NPN-NC/NO, 3-Wire
OTHER NAMES	E2A/M12KS04/M1/C3 E2AM12KS04M1C3
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.157" (4mm) IP67, IP69K Cylinder, Threaded - M12