

E2A-M12KS04-WP-B1 12M

Product description	PROXIMITY SENSOR 12MM 4MM PNP
RoHS Status	Lead free / RoHS Compliant
Stock Condition	692 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS



Specifications of E2A-M12KS04-WP-B1 12M

PART NUMBER	E2A-M12KS04-WP-B1 12M
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	PROXIMITY SENSOR 12MM 4MM PNP
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	692 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Cable Leads
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.157" (4mm)
RESPONSE FREQUENCY	1kHz
PACKAGE / CASE	Cylinder, Threaded - M12
OUTPUT TYPE	PNP-NO, 3-Wire
OTHER NAMES	E2A-M12KS04-WP-B1 12M-ND E2A-M12KS04-WP-B112M E2A/M12KS04/WP/B1 12M E2AM12KS04WPB112M
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.157" (4mm) IP67, IP69K Cylinder, Threaded - M12